

iDFace

Facial identification access controller

With a modern, intuitive design, iDFace from Control iD is an ideal solution for monitoring and managing building access using advanced facial identification technology.

Two 1080p Full HD cameras
(visible + infrared)

3.5" TFT LCD capacitive
touchscreen display

Identification of up to
30,000 faces* with
face liveness detection

TCP/IP, USB, Wi-Fi*, and
Bluetooth* connectivity

IP65 ingress
protection rating

Integrated SIP intercom*
with built-in speaker and
microphone



Operates as a standalone
access control system or
integrates seamlessly with
other systems such as
ASSA ABLOY Primo.

* Available on select models



Touchless

Secure facial recognition
with liveness detection
enables fast, contactless
access – even with masks



Flexible

Choose from face, PIN, RFID,
or QR code identification
to suit different users and
access scenarios



Connected

Built-in connectivity and
intercom combine access
control and communication
in one device



Intuitive

Touchscreen interface
and web-based software
simplify setup and
management

Technical specifications



Access control

Number of users	More than 200,000 registered users
Number of faces	Up to 30,000 faces* with face liveness detection
Access rules	According to schedules and departments
Door control	Via external access control module 1 REX button input, 1 open door sensor
Relay output	1 relay on the external access control module rated up to 30 VAC / 5A
Wiegand input / output	1 / 1 native port



Interconnectivity

Ethernet	1 native 10/100 Mbps Ethernet port
USB	1 USB 2.0 Host port
RS-485	1 RS-485 port for communication between the external access control module and terminal
Wi-Fi	Wi-Fi connection module*
SIP intercom	Integrated G.711-compatible SIP intercom (Pro)*



Identification methods

Facial identification	Two 1080p Full HD cameras (visible light and infrared light)
Proximity reader*	MIFARE® or 125 kHz ASK or HID
Password	User identification through PIN and password
QR code	User identification through QR code



User interface

Display	3.5" TFT color LCD display (320 x 480 px) with capacitive touchscreen
Integrated web software	Complete access control management from your browser
Audio	Built-in speaker and microphone



General characteristics

Dimensions (W x H x D)	Terminal: 76.7 x 174 x 54.5 mm External access control module: 52 x 52 x 22 mm
Equipment weight	Terminal: 240 g External access control module: 35 g
Power input	External 12V 2A source
Ingress protection rating	IP65



Certifications

Markets	CE FCC UKCA ISED*
---------	-------------------------

* optional / available on select models