

Wooden Doorset, Office Entrance - Single

Application

ASSA ABLOY Security Solution Middle East solution for an office admin door with fire rated single leaf wooden door. Equipped with Aperio® wireless access control and Cam-Motion® concealed door closer.

Characteristics

- Full range of sizes
- Noise insulation properties 36dB
- Door Leaf is of high density and medium density mineral board with MDF & Hardwood Lipping
- Door frames are made of solid wood
- Door leaf and frame in PU paint

Performance

- BS approval
- Resistance to sound transmission and acts like a sound barrier
- Acoustic rating available up to 36dB
- Usage: Internal

Safety

- Fire rating up to BS 60 min
- Finger guard option

Sustainability

- Complies to the Green Building Requirement
- FSC sourced wood / Wood Composite materials
- Manufactured under ISO 9001:2015 certification

Hardware Set

- Ball Bearing Butt Hinge, Standard: BS EN 1935:2002. CE Marked.
- Mortice Lock case silent latch Sash lock, Standard: BS EN 12209:2003, CE Marked. (EPD-ASA-20130279-IBC1-EN)
- Aperio® Access control Lever handle with Escutcheon, IP 5, CE Marked. (EPD-ASA-20150279-IAB1-EN)
- MKS Knob Cylinder, Standard: BS EN 1303:2015, BS EN 15804 and SKG approved. (EPD-ASA-20170150-IBA1-EN)
- Concealed door closer Cam-Motion, Standard: BS EN 1154. CE Marked.
- Floor mounted door stop.
- Self-adhesive seal
- Intumescent seal.

Typical applications

- Commercial buildings, hospitals, school, hotels.



Compatible Standards: BS EN1935, BS EN1154, BS EN12209, BS EN 1303, BS EN14351-1, BS476 pt22, BS EN1634-1.