

ASSA ABLOY CARE AND MAINTENANCE RECOMMENDATIONS

IN ORDER TO GAIN THE MAXIMUM LIFE FROM YOUR ASSA ABLOY PRODUCT, CORRECT MAINTENANCE PROCEDURES SHOULD BE FOLLOWED.

The following guidelines provide recommendations for your maintenance program. It is important that maintenance be done on a regular basis. It is recommended that inspections and cleaning be done routinely – at least annually.

A shorter interval should be used in marine or other corrosive environments and in areas prone to atmospheric fallout.

1. The complete window or door should be inspected regularly to ensure that it is still in good working order. Such things as the faulty hinges, warped windows and doors, and or distorted frames can put excessive load on other components reducing their operating life.
2. Dirt, grime and airborne salt deposits are often capable of causing damage to the product's surfaces and mechanism, including the cylinder barrel, and must be regularly removed.
3. The following cleaning process is recommended for Mechanical Products:
 - Cleaning should be done with a dilute solution of a mild liquid detergent in warm water. Avoid excessively hot solutions.
 - Use a soft bristle brush or similar to clean the surface. Do not use abrasive tools.
 - After cleaning, rinse surfaces thoroughly with fresh water.
 - Do not use strong solvent type cleaners on surfaces. Where it is necessary to remove materials from the surface (such as adhesives and a solvent is necessary) the weakest possible solvent should be used. The only solvents recommended are methylated spirits, white spirits or Isopropanol. Ensure the contact time for the solvent is kept to a minimum and that the solvent is thoroughly rinsed from the surface. A small test area should be checked prior to solvent cleaning to ensure that no damage to the film or colour change will occur.
 - Where more aggressive cleaning is required, a very mild abrasive such as a high quality automotive cream polish, used in accordance with the manufacturer's instructions, may be necessary. The use of strongly abrasive compounds such as cutting compounds is not recommended.
 - The use of bore water for cleaning is not recommended due to its mineral content, as it can bring about staining of the coating and may instigate long term coating failure.

- Ensure cleaning fluids do not penetrate into the lock or cylinder.
4. The following cleaning process is recommended for Electromechanical Products:
 - Cleaning should be done only on external surfaces only.
 - Use a damp cloth with a diluted solution of a mild detergent in warm water. Avoid excessively hot solutions.
 - Ensure mild liquid detergent fluids do not penetrate into the lock or cylinder.
 - Do not use abrasive tools or solvents.
 - After cleaning, remove any excess water using a soft cloth.
 - The use of bore water for cleaning is not recommended due to its mineral content, as it can bring about staining of coating and may instigate long term coating failure.

Change batteries for Electromechanical Products when the low battery indicator is displayed (see User's Guide for any battery type requirements)

The use of products with soft finishes; such as gold plate, lacquered brass or chrome plate, need special care. Dirt or other contaminants must not be allowed to build up on the surface, as these will readily discolour and impair the surface.

Some change in colour, gloss or chalking may be expected dependant on exposure.

Key cylinders should be lubricated at least once a year or when there are signs of roughness when inserting or retracting the key. Remove any dirt, grime and salt deposits on and around the end of the cylinder barrel, and apply a small amount of lubricant to the keyblade and insert the key into the lock barrel to maintain a smooth action. Cylinders should be lubricated with 'Inox MX3' lubricant.

Products such as spiral spring balances and the stays are installed during window manufacturing process and are a component of a window system that are subject to fitment and environmental factors, please contact the window manufacturer for recommended maintenance of your window system.

Exposed mechanisms and parts should be cleaned with a non-metallic brush. Apply a small amount of preferably Teflon based lubricant or alternatively light sewing machine 5W mineral oil to lubricate moving parts and prevent corrosion of exposed metal surfaces. Be careful not to apply an excessive amount of lubricant as this will have a detrimental effect of adhering dust to these surfaces, potentially reducing their life.