

# Key eCLIQ N109,V=PR/PSM/PN

Programming key - no locking function

**IKON**  
ASSA ABLOY



## Product description

- Transfers up to 3,000 programming steps to cylinders
- Can read out up to 6,000 events from the cylinders and transmit these to software
- Electronic authorisation confirmation within the software
- Protected by a 6-digit individual PIN code
- Electronic key and locking system encryption
- Optical and acoustic signals for indicating programming tasks and battery status
- The data and power transmission to the cylinder is contact based
- The data transmission to the cylinder is highly encrypted
- Temperature range 0° C to +70° C (ATEX -30° C to +50° C)
- Protected against temporary immersion in water (IP67)
- Power supply via commercially-available lithium battery (CR2450)\*
- The battery can be easily changed by the user without tools
- Optional, additional lower ranking programming keys can be supplied for a locking system (N0.003,V=PN und N0.003,V=PSM)
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (ATEX=II 2G EX IB IIB T4 Gb)\*

## Scope of delivery

- 1 programming key incl. battery\*

## Note

- \*The standard eCLIQ battery is not approved for ATEX, only the special battery must be used

## Variants that can be ordered

Article number	V=
N109,V=PR/PSM/PN	PR
	PSM
	PN

## Suitable ASSA ABLOY products

Order number	Product
NP04	Desk programming device set eCLIQ / CLIQ® Go
NR01	Wall programming device eCLIQ-Remote
NR03	Vandalism proof wall programming device eCLIQ-Remote
XS13/XS17	CLIQ Web Manager

