

Vandalism proof wall programming device eCLIQ- Remote NR03

Fixed-site station for programming eCLIQ user keys

IKON
ASSA ABLOY



Overview of Advantages

- Supports PoE (Power over Ethernet) or external power supply 12-24 V
- Connection and data exchange via network cable

Product description

- Connected by standard network cable
- Suitable for outdoor usage and vandalism hazard areas
- Permits changes to times and authorisations (depending on key type) as well the read-out of event logs
- Optionally with floating contact for third-party devices (V=FO1) only with V=E3 keys
- Core exchange module for easy changing of the core by external influence
- Acoustic and optical signals for operating status and activity progress
- Brightness of the LED display changeable
- Supports PoE (Power over Ethernet) or external power supply 12-24 V
- Splash-proof (SUR=0) IP45
- Optionally available with dust and rain cover (SUR=1) IP65
- Vandalism-resistant IK9
- Organisation number selectable and visible at the front
- Requirement for using V=FO1: key firmware eCLIQ 16.3.3 or VERSO/+CLIQ 16.3.7 or higher

Scope of delivery

- 1 vandalism proof wall programming device

Variants that can be ordered

Article number

NR03

Suitable ASSA ABLOY products

| Order number | Product |
|-----------------|------------------|
| XS13/XS17 | CLIQ Web Manager |
| N109,V=E1 | Key eCLIQ |
| N109,V=E2 | Key eCLIQ |
| N109,V=E3 | Key eCLIQ |
| N109,V=B1/B2/B3 | Key eCLIQ |
| N110,V=E2 | Key eCLIQ |
| N110,V=E3 | Key eCLIQ |
| N111,V=E1 | Key eCLIQ |
| N111,V=E2 | Key eCLIQ |
| N111,V=E3 | Key eCLIQ |
| N112,V=E1 | Key eCLIQ |

Accessories/Individual parts

| Order number | Product |
|--------------|--|
| NE34 | Corechanging module |
| NZ05 | Power supply for wall programming device (flush-mounted) |
| VZ01 | Power supply |
| VZ08 | Mini USB adapter |

