Entrance Door with Escape Control and Push Bar



Solution family: Exterior Door Solution

Solution group: Single-Steel/Aluminium-Self Closing-Panic

Device-Escape Route

Description

ASSA ABLOY Sicherheitstechnik Solution for an escape route monitored single leaf aluminium or steel door. The door status (open or closed) is monitored via a door contact and the door can be authorised for release using a key switch. An alarm is triggered if the door is opened without authorisation.

Equipped with an OneSystem self-locking panic mortise lock and Door closer with Cam-Motion® technology. The lock/door is automatically self-locked as soon as the door closer has closed the door.

Typical applications:

Education, School, University, Hotel, Hospital, Stadium, Multi Arena, Museum, Gallery, Shopping Mall, Bank, Industry, Office, Commercial, Congress, Health Care

Hardware Set

- Security Panic Lock Mechanical, OneSystem, Standard: EN 179 and EN 1125
- Security Fitting Half-set, Knob outside, OneSystem, Standard: DIN EN 1906 and DIN 18273
- Door Closer Cam-Motion®, Standard: DIN EN 1154
- Panic Push Bar, OneSystem, Standard. EN 1125, EN 1634, EN 15804
- Door Surveillance System
- Key Switch Outside
- Reed Contact



Exterior



Interior