

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	ASSA ABLOY Entrance Systems AB
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-ASA-20250464-IBA1-EN
Issue date	04.02.2026
Valid to	03.02.2031

ASSA ABLOY FD2350P Manual folding door ASSA ABLOY Entrance Systems

www.ibu-epd.com | <https://epd-online.com>



1. General Information

ASSA ABLOY Entrance Systems

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-ASA-20250464-IBA1-EN

This declaration is based on the product category rules:

Windows and doors , 01.08.2021
(PCR checked and approved by the SVR)

Issue date

04.02.2026

Valid to

03.02.2031



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

ASSA ABLOY FD2350P Manual folding door

Owner of the declaration

ASSA ABLOY Entrance Systems AB
Lodjursgatan 10
SE-261 44 Landskrona
Sweden

Declared product / declared unit

This declaration represents 1 manually operated industrial folding door, 4050 mm wide and 4000 mm high, consisting of 4 panels, 4 glass windows and inside installation. Panels are filled with CFC-free polystyrene, panel thickness 57 mm and panel height 4000 mm. Windows are double-sided insulated hardened glass, rectangular, in plastic frame.

Scope:

This declaration and its LCA study are relevant to the ASSA ABLOY FD2350P Manual folding door. The production location is in Lidköping, Sweden, and components are sourced from international tier one suppliers. FD2350P Manual folding door sizes vary according to project requirements; a standard door 4050 mm wide and 4000 mm high with insulated panels filled with CFC-free polystyrene, panel thickness 57 mm, panel height 4000 mm, is used in this declaration.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally



Dr.-Ing. Wolfram Trinius,
(Independent verifier)

2. Product

2.1 Product description/Product definition

Product name: ASSA ABLOY FD2350P Manual

Product characteristic: Folding Door

The ASSA ABLOY FD2350P manual folding door is a well-insulated folding door especially developed for demanding industrial environments. High flexibility makes it possible to install this door in almost every type of building.

The door slides (folds) to the left or right or in both directions if it is in two parts, leaving the door opening completely free, allowing free space around the door opening. The door can be installed on either the inside or the outside of the exterior wall. The door is made of insulated panels. The panels are designed without thermal bridge to provide minimal thermal transmittance, which reduces energy cost. The surface is made of rilled steel sheet. There is top, bottom and side seals and seals between door sections. The standard track system is made of galvanized steel.

The door has 5 primary parts:

- 1) Door leaf
- 2) Seals
- 3) Hardware
- 4) Passdoor (optional)
- 5) Windows (optional)

The ASSA ABLOY FD2350P manual folding door has been designed to meet all operational and safety requirements in the European Directives and the standards issued by the European Standardization Committee, CEN.

Harmonised European standards, which have been applied:

For the placing of the product on the market in the EU/EFTA (with the exception of Switzerland) the Regulation (EU) No. 305/2011/ (CPR) and the following other harmonization provisions apply:

Directive (EU) 2006/42/EC Machinery Directive (MD) and Directive (EU) 2014/30/EU Electromagnetic Compatibility Directive (EMCD) respectively and 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS), Directive 2012/19/EU Waste Electrical and Electronic Equipment (WEEE Directive) respectively apply.

The product needs a Declaration of Performance in accordance with the CPR taking into consideration: EN 13241+A2:2016 Industrial, commercial, garage doors and gates - Product standard, performance characteristics, and the CE-marking. The CE-marking for the product takes into account the Declaration of Performance in accordance with the CPR and the proof of conformity with the following harmonised norms based on the other harmonisation provisions.

- EN 13241+A2:2016
- EN 12428:2013
- EN 12453:2017+A1:2022
- EN 12604:2017+A1:2020 EN 13241+A2:2016

For thermal insulation, the standard EN 12428:2013-04 applies.

The folding door has not performed tests regarding fire

resistance or sound insulation. For the application and use, the respective national provisions apply.

2.2 Application

The ASSA ABLOY FD2350P manual folding door is suitable for all types of buildings, with regards to both function and appearance. It has a modern, clean design and its high flexibility makes it possible to install this door in almost every type of building allowing free space around the door.

2.3 Technical Data

The technical properties of the declared FD2350P manual folding door are following:

- Height¹: 4000 [mm]
- Width¹: 4050 [mm]
- Panel thickness: 57 [mm]
- Panel material: CFC-free polystyrene with sheet metal inner and outer skins
- Resistance to wind load acc. to EN 12424: Class 5**
- Thermal transmittance acc. to EN 12428: 1,23 [W/M²K]^{***}
- Resistance to water penetration acc. to EN 12426: Class 3****
- Air permeability acc. to EN 12426: Class 5****

¹) Other sizes available, maximum height: 6000 mm and maximum width: 7500 mm

**DLW² 5000 mm *DLH³ 5000 mm

*** Door configuration 4000 mm * 4000 mm

****DLW² 3500 mm * DLH³ 3100 mm

²Daylight Width

³Daylight Height

Constructional data

Name	Value	Unit
Heat transfer coefficient glass acc. to EN 674 / EN 675	1.1	W/(m ² K)
Heat transfer coefficient of the entire door or gate system	1.41	W/(m ² K)
Burglar protection class acc. to EN 1628	Class 1	-
Joint permeability coefficient acc. to EN 1026	Class 5	-
Water tightness acc. to EN 12425	Class 3	-
Resistance to wind load acc. to EN 12424	Class 5	-
Heat transfer coefficient panel acc. to EN 12428	1.29	W/(m ² K)

Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to EN 13241:2003+A2:2016.

2.4 Delivery status

ASSA ABLOY FD2350P manual folding door unit with door size: width 4050 mm and height 4000 mm, is delivered ready for installation.

2.5 Base materials/Ancillary materials

The average composition for declared FD2350P manual folding door, is as following:

Name	Value	Unit
Aluminium	6,3	%
Lead	0.01	%
Plastics	13.6	%
Steel	69,9	%
Glass	10.2	%
TOTAL	100.0	%

*Percentage in mass

2.6 Manufacture

The primary manufacturing processes are made by Tier 1 suppliers. The components have origin in processes such as stamped steel, turning and steel casting. The final manufacturing processes for folding door units occur in Lidköping, Sweden.

Offcuts and scraps during the manufacturing process are directed to a recycling unit. Waste is sent for disposal. Waste codes according to the European Waste Catalogue and Hazardous Waste List - Valid from 1 July 2015.

EWC 12 01 01 Ferrous metal filings and turnings
EWC 12 01 03 Non-ferrous metal filings and turnings
EWC 17 02 03 Plastic
EWC 17 04 01 Copper, bronze, brass
EWC 17 04 02 Aluminium
EWC 17 04 05 Iron and steel
EWC 17 04 11 Cables with the exception of those outlined in *EWC 17 04 10*
EWC 20 01 39 Polystyrene foam

2.7 Environment and health during manufacturing

ASSA ABLOY is committed to producing and distributing door opening solutions with minimal environmental impact, where health & safety are the primary focus for all employees and associates.

- Environmental operations, GHG (Greenhouse Gas), energy, water, waste, Volatile organic compounds (VOC), surface treatment and H&S are routinely monitored. Inspections, audits, and reviews are conducted periodically to ensure that applicable standards are met and to evaluate the effectiveness of the environmental management program.
- The Code of Conduct covers human rights, labor practices and decent work. Management of ASSA ABLOY is aware of their environmental roles and responsibilities, providing appropriate training, supporting accountability and recognizing outstanding performance.
- Any waste metals during machining are separated and recycled. Waste water from water-based painting processes is delivered to waste treatment plant.

2.8 Product processing/Installation

The folding door components are supplied ready for installation. The panels, tracks and hardware are assembled and installed on-site. The components are assembled using simple tools including drills and hand tools. The installation is performed by skilled installation technicians.

2.9 Packaging

The ASSA ABLOY FD2350P manual folding door is placed horizontally on wooden pallets and banded to pallet for shipment. Minimum of 1 and maximum 10 doors per pallet.

Material Value

Wood: 98.6%
 Plastics: 0.3%
 Paper: 1.1%

TOTAL 100%

All materials incurred during installation are dealt with at the construction site.

Waste codes according to the European Waste Catalogue and Hazardous Waste List - Valid from 1 July 2015.

- *EWC 15 01 01* Paper and cardboard packaging
- *EWC 15 01 02* Plastic packaging
- *EWC 15 01 03* Wooden packaging

2.10 Condition of use

Regular inspection is recommended. If serious damage is found, contact the ASSA ABLOY service department.

Monthly examination:

Check the screw attachments and nuts between door leaf, hinges, tracks, bearing brackets C-channels and installation frames. Make sure that all seals are clean, intact and undamaged. Clean them if necessary.

Examination every second month:

Clean the upper track if needed. Check the hinges and door leaves. Look for damage. Check the bearing brackets and their attachments. Look for damage.

Examination every six months:

Clean the inside and outside of the door with water and a mild detergent. This way, the durability of the door is extended. Look for damage on the surface. Surface damage must be improved according to the manufacturer's instructions.

2.11 Environment and health during use

There is no harmful emissive potential. No damage to health or impairment is expected under normal use corresponding to the intended use of the product.

2.12 Reference service life

The product has a reference service life of 200.000 cycles which complies to 10 years of standard daily use (with the recommended yearly service check). For this EPD, the lifetime of 10 years was considered. The location and intended use of the steel door assembly, the environment to which it is exposed, and the cycling of the door assembly will determine the steel door life expectancy.

2.13 Extraordinary effects

Fire

The folding door is not fireproof and is not approved for use in fire/smoke areas. The product has not been tested for reaction to or resistance to fire/smoke.

Water

The product does not contain any substances that could be released and have a negative impact on the water quality in case of flood.

Mechanical destruction

No danger to the environment can be anticipated during mechanical destruction.

2.14 Re-use phase

The product is possible to re-use during the reference service life and can be moved from one docking station to another. The majority, by weight, of components is steel, which can be recycled. The plastic components can be used for energy recovery within a waste incineration process.

All recyclable materials are directed to a recycling unit where they are recycled (steel, electronics and electro-mechanics). On the other hand, the plastic components are sent to the waste incineration plant for their energy recovery.

Waste codes according to the European Waste Catalogue and Hazardous Waste List - Valid from 1 July 2015:

- EWC 17 04 05 Iron and steel

- EWC 17 04 01 Copper, bronze, brass
- EWC 17 04 02 Aluminium
- EWC 17 02 03 Plastic
- EWC 17 02 02 Glass
- EWC 15 01 03 Wooden packaging

2.15 Disposal

The product can be mechanically disassembled to separate the different materials. The majority, of components are steel which will be recycled. The plastic components are used for energy recovery in an incineration plant. No disposal is foreseen for the product or for the corresponding packaging.

2.16 Further information

ASSA ABLOY Entrance Systems AB
Lodjursgatan 10
SE-261 44 Landskrona
Sweden

www.assaabloyentrance.com

3. LCA: Calculation rules

3.1 Declared Unit

The declaration refers to the functional unit of 1 piece of ASSA ABLOY FD2350P Manual folding door as specified in Part B requirements on the EPD IBU: PCR Automatic doors, automatic gates, and revolving door systems (door systems)

Declared unit and mass reference

Name	Value	Unit
Mass (without packaging)	378.07	kg
Mass packaging (paper wood, copper and plastics)	21.16	kg
Declared unit for sectional door systems (dimensions acc. to this PCR)	1	pce
Mass reference	378.07	kg/pce
Declared unit	1	pce

3.2 System boundary

Type of the EPD: cradle to gate - with options. The following life cycle stages were considered:

Production stage:

- A1 – Raw material extraction and processing
- A2 – Transport to the manufacturer and
- A3 – Manufacturing

Construction stage:

- A4 - Transport from the gate to the site
- A5 – Packaging waste processing

End-of-life stage:

- C1 - De-construction/demolition
- C2 – Transport to waste processing,
- C3 – Waste processing for recycling and
- C4 – Disposal (landfill, waste for incineration).

This includes provision of all materials, products and energy, packaging processing and its transport, as well as waste processing up to the end-of-waste state or disposal of final residues.

- Benefits and loads beyond the system boundaries: D – Declaration of all benefits and loads.

3.3 Estimates and assumptions

Transportation: Data on the mode of transport and distances, as reported by suppliers were used for those materials and parts contributing more than 2% of the total product mass.

Use stage: Since the ASSA ABLOY FD2350P Manual folding door does not require energy for its operation, the use phase is not considered in this EPD.

EoL: In the End-of-Life stage, for all the materials from the product which can be recycled (steel, aluminum, electronic parts, electro-mechanics, copper, stainless steel and brass), a recycling scenario with 100% collection rate was assumed. The plastic components are sent for energy recovery within a waste incineration process.

EoL is assumed to happen within EU-28. Furthermore, a transport distance by truck of 100 km has been assumed in the model.

3.4 Cut-off criteria

In the assessment, all available data from the production process are considered, i.e. all raw materials used, auxiliary materials (e.g. lubricants), and electric power consumption - including material and energy flows contributing less than 1% of mass or energy (if available). In case a specific flow contributing less than 1% in mass or energy is not available, worst case assumption proxies are selected to represent the respective environmental impacts.

Impacts relating to the production of machines and facilities required during production are out of the scope of this assessment.

3.5 Background data

For life cycle modelling of the considered product, Sphera's Life Cycle for Expert (LCA FE) software is used. Sphera Managed Lifecycle Content (MLC) modelling database is used as the background database of the study.

3.6 Data quality

The requirements for data quality and background data correspond to the specifications of the IBU PCR Part A. Sphera performed a variety of tests and checks during the entire project to ensure a high quality of the completed project.

This obviously includes an extensive review of project-specific LCA models as well as the background data used. The technological background of the collected data reflects the physical reality of the declared products.

The datasets are complete and conform to the system boundaries and the criteria for the exclusion of inputs and outputs.

All relevant background datasets are taken from the *Sphera MLC database*.

3.7 Period under review

The period under review is 2023 (12-month average).

3.8 Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Europe

3.9 Allocation

Regarding incineration, the software model for the waste incineration plant (WIP) is adapted according to the material composition and heating value of the combusted material. In this EPD, the following specific life cycle inventories for the WIP are considered:

- Waste incineration of paper
- Waste incineration of Plastic
- Waste incineration of Wood

Regarding the recycling material of metals, the metal parts in the EoL are declared as end-of-waste status. Thus, these materials are considered in module D. Specific information on allocation within the background data is given in the MLC dataset documentation.

3.10 Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Sphera's Managed LCA Content CUP 2020.1 serves as background database for the calculation.

4. LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

The following technical information is a basis for the declared modules or can be used for developing specific scenarios in the context of a building assessment if modules are not declared (MND).

Information on describing the biogenic carbon content at factory gate

Name	Value	Unit
Biogenic carbon content in product	-	kg C
Biogenic carbon content in accompanying packaging	10.53	kg C

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

Transport to the building site (A4)

Name	Value	Unit
Kg of fuel diesel with maximum load (27t payload)	27.51	kg/100km
Transport distance truck (primary target market is EU 28)	500.00	km
Capacity utilization (incl. empty runs) of truck	61.00	%

Installation into the building (A5)

Name	Value	Unit
Output substances following waste treatment on site (paper/cardboard packaging)	0.24	kg
Output substances following waste treatment on site (wood packaging)	20.86	kg
Output substances following waste treatment on site (plastic packaging)	0.06	kg

Reference service life

Name	Value	Unit
Reference service life	20	years

End of life (C1-C4)

Name	Value	Unit
Transport to EOL	100	km
Collected separately aluminum, steel, lead, plastics and glass	339.57	kg
Incineration of plastic parts	51.28	kg
Recycling aluminium, lead and steel	288.32	kg
Landfill	38.40	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Collected separately waste type (including packaging)	360.82	kg
Recycling aluminium	6.65	%
Recycling steel	73.26	%
Recycling lead	0.01	%
Incineration of plastic parts	14.23	%
Incineration of packaging (paper, wood and plastic) (from A5)	5.86	%

5. LCA: Results

Results shown are calculated according to EN 15804+A2.

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 piece ASSA ABLOY FD2350P Manual folding door

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	6.67E+02	1.21E+01	3.4E-01	0	2.3E+00	1.67E+02	4.03E-01	-4.49E+02
GWP-fossil	kg CO ₂ eq	7.04E+02	1.08E+01	8.52E-03	0	2.05E+00	1.29E+02	4.37E-01	-4.48E+02
GWP-biogenic	kg CO ₂ eq	-3.84E+01	1.2E+00	3.32E-01	0	2.27E-01	3.85E+01	-3.46E-02	-4.62E-01
GWP-luluc	kg CO ₂ eq	6.04E-01	9.75E-02	5.6E-06	0	1.85E-02	4.58E-03	1.26E-03	-1.25E-01
ODP	kg CFC11 eq	1.58E-09	2.21E-15	6.13E-17	0	4.19E-16	3.79E-14	1.62E-15	4.65E-11
AP	mol H ⁺ eq	2.41E+00	1.36E-02	9.53E-05	0	2.59E-03	6.25E-02	3.13E-03	-1.56E+00
EP-freshwater	kg P eq	1.42E-03	3.67E-05	1.2E-08	0	6.95E-06	6.42E-06	7.5E-07	-2.11E-04
EP-marine	kg N eq	4.95E-01	4.13E-03	3.44E-05	0	7.83E-04	1.58E-02	8.07E-04	-2.45E-01
EP-terrestrial	mol N eq	5.36E+00	4.92E-02	4.29E-04	0	9.32E-03	2E-01	8.86E-03	-2.66E+00
POCP	kg NMVOC eq	1.57E+00	1.13E-02	9.12E-05	0	2.13E-03	4.96E-02	2.44E-03	-7.83E-01
ADPE	kg Sb eq	1.22E+04	1.61E+02	1.07E-01	0	3.04E+01	5.08E+01	5.73E+00	-5.1E+03
ADPF	MJ	1.12E-02	9.74E-07	9.69E-10	0	1.84E-07	5.61E-07	3.92E-08	-3.23E-05
WDP	m ³ world eq deprived	4.92E+01	1.17E-01	4.22E-02	0	2.22E-02	1.47E+01	4.58E-02	-3.5E+01

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 piece ASSA ABLOY FD2350P Manual folding door

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	3.25E+03	9.29E+00	4.02E+02	0	1.76E+00	1.03E+01	7.5E-01	-1.28E+03
PERM	MJ	4.02E+02	0	-4.02E+02	0	0	0	0	0
PERT	MJ	3.65E+03	9.29E+00	1.95E-02	0	1.76E+00	1.03E+01	7.5E-01	-1.28E+03
PENRE	MJ	1.02E+04	1.61E+02	1.25E+00	0	3.06E+01	2.1E+03	5.73E+00	-5.11E+03
PENRM	MJ	2.05E+03	0	-1.14E+00	0	0	-2.05E+03	0	0
PENRT	MJ	1.23E+04	1.61E+02	1.07E-01	0	3.06E+01	5.08E+01	5.73E+00	-5.11E+03
SM	kg	2.66E+02	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0
FW	m ³	5.35E+00	1.08E-02	9.93E-04	0	2.05E-03	3.48E-01	1.45E-03	-3.32E+00

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 piece ASSA ABLOY FD2350P Manual folding door

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	4.18E-05	7.46E-06	1.58E-10	0	1.41E-06	1.72E-07	8.74E-08	-2.64E-06
NHWD	kg	3.02E+01	2.56E-02	1.07E-02	0	4.84E-03	1.26E+01	2.88E+01	-5.61E+01
RWD	kg	1.07E+00	2.97E-04	5.65E-06	0	5.63E-05	2.07E-03	6.51E-05	-2.33E-01
CRU	kg	0	0	0	0	0	0	0	0
MFR	kg	1.34E+01	0	2.4E-01	0	0	3.48E+02	0	0
MER	kg	0	0	0	0	0	0	0	0
EEE	MJ	0	0	5.15E-01	0	0	3.88E+02	0	0

EET	MJ	0	0	9.34E-01	0	0	6.59E+02	0	0
-----	----	---	---	----------	---	---	----------	---	---

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 piece ASSA ABLOY FD2350P Manual folding door

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	Disease incidence	2.81E-05	9.18E-08	5.28E-10	0	1.74E-08	4.33E-07	3.88E-08	-1.74E-05
IR	kBq U235 eq	1.24E+02	4.39E-02	8.74E-04	0	8.31E-03	2.67E-01	6.69E-03	-4.64E+01
ETP-fw	CTUe	5.87E+03	1.2E+02	5.1E-02	0	2.28E+01	3.71E+01	3.27E+00	-1.42E+03
HTP-c	CTUh	5.05E-07	2.49E-09	2.7E-12	0	4.71E-10	4.65E-09	4.85E-10	-4.06E-07
HTP-nc	CTUh	1.54E-05	1.26E-07	1.17E-10	0	2.4E-08	4.43E-07	5.35E-08	-3.85E-06
SQP	SQP	7.55E+03	5.64E+01	2.85E-02	0	1.07E+01	1.26E+01	1.19E+00	-2.01E+02

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

6. LCA: Interpretation

This chapter contains an interpretation of the Life Cycle Impact Assessment categories. Stated percentages in the whole interpretation are related to the overall life cycle, excluding credits (module D).

The production stage (modules A1-A3) contributes between 78% and 98% to the overall results for all core environmental impact assessment categories, except for the global warming potential – biogenic (GWP-biogenic). This result is mainly related to the extraction of renewable raw materials (A1).

Within the production stage, the main contribution to all the

impact categories is the production of steel and aluminum mainly due to the energy consumption of these processes. These two materials account for approx. 70% of the overall mass of the product, therefore, the impacts are in line with the mass composition of the product. The environmental impacts for transport (A2) have a negligible impact within this stage.

In the end-of-life stage, there are loads and benefits (module D, negative values) considered. The benefits are considered beyond the system boundaries and are declared for the recycling potential of the metals and for the credits from the incineration process (energy substitution).

7. Requisite evidence

Not applicable in this EPD. 7.2 MDI
MDI (4,4' Methylene bisphenyl isocyanate) measurement according to:
- NIOSH (National Institute for Occupational Safety and Health) Physical and Chemical Analytical Method 142 (P&CAM142), or
- BIA 7670, or
- RAL UZ-76

Note: The analytics of these methods are identical.

7.3 Checking for pretreatment of the substances used Measurement according to AltholzVO (only applicable in Germany) (wood protective agent substances, heavy metals, etc.). Only applicable for wood materials indicating "scrap wood" as a resource in their base materials. 7.4 Fire gas toxicity

Measuring according to DIN 53436. Optional indication; for wood materials used in meeting places, this measurement is mandatory

Note:

DIN 53436 is the test standard to which DIN 4102-1 refers. In this respect, PCR compliant tests are to be assumed for indication of DIN 4102-1. 7.5 VOC emissions

Optional for Products

with exclusively external application. Test method according to AgBB

schematic with Measuring point / date and Result indication as value range (VOC indication is optional where validity is shorter (1 year)):

AgBB overview of results (28 days [µg/m³])

Name	Value	Unit
TVOC (C6 - C16)		µg/m³
Sum SVOC (C16 - C22)		µg/m³
R (dimensionless)		-
VOC without NIK		µg/m³
Carcinogenic Substances		µg/m³

AgBB overview of results (3 days [µg/m³])

Name	Value	Unit
TVOC (C6 - C16)		µg/m³
Sum SVOC (C16 - C22)		µg/m³
R (dimensionless)		-
VOC without NIK		µg/m³
Carcinogenic Substances		µg/m³

8. References

CPR

Regulation (EU) No. 305/2011, Construction Product Regulation (CPR)- laying down harmonized conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

DIN EN ISO 10140-2

DIN EN ISO 10140-2:2010, Acoustics - Laboratory measurement of sound insulation of building elements - Part 2: Measurement of airborne sound insulation (ISO 10140-2:2010); German version EN ISO 10140-2:2010

DIN EN ISO 13849-1

DIN EN ISO 13849-1:2016, Safety of machinery - Safety-related parts of control systems - Part 1: General principles for design

DIN 4102

DIN 4102-1 B2:1998, Reaction to fire tests - Ignitability of building products subjected to direct impingement of flame.

DIN EN 12424

DIN EN 12424:2000, Industrial, commercial and garage doors and gates - Resistance to wind load - Classification; German version EN 12424:2000

DIN EN 12426

DIN EN 12424:2000, Industrial, commercial and garage doors and gates. Air permeability. Classification; German version EN 12424:2000

DIN EN 12428

DIN EN 12428:2013, Industrial, commercial and garage doors - Thermal transmittance - Requirements for the calculation; German version EN 12428:2013

DIN EN ISO 14025

DIN EN ISO 14025:2010, Environmental labels and declarations - Type III environmental declarations - Principles and procedures

EN ISO 10140-2

EN ISO 10140-2:2010, Acoustics - Laboratory measurement of sound insulation of building elements - Part 2: Measurement of airborne sound insulation (ISO 10140-2:2010); German version EN ISO 10140-2:2010

EN 12425

EN 12425:2000, Industrial, commercial and garage doors and gates - Resistance to water penetration - Classification; German version EN 12425:2000

EN 12453

EN 12453:2017, Industrial, commercial and garage doors and gates – Safety in use of power operated doors – Requirements and test methods

EN 13241-1

EN 13241:2003+A2:2016, Industrial, commercial, garage doors and gates - Product standard, performance characteristics

EN 15804+A2

EN 15804:2014+A2:2020, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

EN 61000-6-2

EN 61000-6-2:2005, Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity for industrial environments

EN 61000-6-3

EN 61000-6-3:2007: Electromagnetic compatibility (EMC) - Part 6-3: Generic Standards - Emission standard for residential, commercial and light-industrial environments

EWC European Waste Catalogue established by Commission Decision 2000/532/EC

ISO 9001

ISO 9001:2015, Quality management systems - Requirements with guidance for us

Regulation (EU) No 305/2011

Regulation of the European parliament and the council laying down harmonized conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

2006/42/EC

European directive on machinery, and amending Directive 95/16/EC (recast)

2011/65/EC

European directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment, and its amendment directives including 2015/863/EC (RoHS directive)

2012/19/EU

European directive on waste electrical and electronic equipment (WEEE)

2014/30/EU

European directive on the harmonization of the laws of the Member States relating to electromagnetic compatibility (recast)

2015/863/EU

European directive amending Annex II to Directive 2011/65/EU of the European Parliament and of the Council as regards the list of restricted substances

Other sources:

Sphera Managed Lifecycle Content (MLC)

Sphera Solutions, Managed LCA content dataset documentation, Sphera Solutions, Chi-cago, US, 2023. Retrieved from <https://sphera.com/product-sustainability-gabi-data-search/>

Sphera's Life Cycle for Expert (LCA FE) software: Sphera Solutions, 'Life Cycle Assessment for Expert software', Sphera Solutions, Chicago, US, 2023. Retrieved from <https://sphera.com/life-cycle-assessment-lca-software/>.

IBU PCR Part A:2019

Institut Bauen und Umwelt e.V., Königswinter (pub.): Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report. Version 1.8 April 2019 www.ibu-epd.de

IBU PCR Part B: Windows and Doors

Institute for Building and Environment (IBU), 2021: PCR

Guidance Texts for Building-Related Products and Services.
From the Environmental Product Declarations Program of the
Institute for Building and Environment (IBU), Part B:
Requirements for the EPD for Windows and Doors. Version 1.4
(01.08.2021) www.ibu-epd.com

IBU 2021

General Instructions for the EPD programme of Institut Bauen

und Umwelt e.V. Version 2.0, Berlin: Institut
Bauen und Umwelt e.V., 2021.
www.ibu-epd.com

TRACI Methodology

Tool for the Reduction and Assessment of Chemical and Other
Environmental Impacts (TRACI), EPA/600/R-12/554 2012



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

Sphera Solutions GmbH
Hauptstrasse 111-113
70771 Echterdingen-Leinfelden
Germany

+49711341817-0
info@sphera.com
www.sphera.com



Owner of the Declaration

ASSA ABLOY Entrance Systems AB
Lodjursgatan 10
SE-261 44 Landskrona
Sweden

+46 (0)10 47 47 000
info@assaabloy.com
www.assaabloyentrance.com