



ASSA ABLOY

TESA Hotel i-programmer

The new, streamlined way to manage your TESA Hotel devices

Faster, fully digital management of TESA Hotel installations

The TESA Hotel i-programmer App simplifies, accelerates, and modernizes the way you configure and maintain your TESA Hotel devices. Designed as a replacement for the traditional Portable Programmer, it brings full system control directly to your smartphone, enabling you to initialize devices, apply updates, collect events, open doors, and manage firmware from one intuitive interface.



Compatible with all
TESA Hotel devices

Optimized for Android phones, the i-programmer gives you complete mobility and flexibility on-site

Download the PC-To-Lock file directly to your phone via email, OneDrive, or local transfer - and manage one or multiple installations effortlessly

Direct device connection via PC-To-Lock + USB-A to USB-C adapter or USB C (depending on the device)



Innovative

A fully mobile experience which transforms traditional management into a faster, more flexible process



Convenient

User friendly interface - clearer navigation and quicker access to essential functions




Secure

Every operation is protected to ensure safe, reliable system management

TESA Hotel i-programmer

Technical information



Technical data and features



General information

i-programmer App

Built using Progressive Web App (PWA) technology
Compatible with Windows and macOS laptops, plus Android smartphones
Not compatible with iOS devices



System requirements

Mobile devices (Android)

Minimum requirements:

- Android 8.0 for Google Chrome with Chrome version 138 or higher
- Android 10.0 for Microsoft Edge with Edge version 140 or higher

Recommended RAM: 2 GB or more. Free storage: 30 MB min. Performance may vary on low end devices with limited RAM

Connectivity: Internet access recommended for file downloads and updates

Required permissions:

- Storage access to read and store PC to Lock files
- USB access for communication with TESA Hotel devices

Typical power consumption:

- 14.7 mA in standby mode (App open or closed)
- 19.0-23.0 mA during operation (initialization, updates, testing, event collection, etc.)

PC, laptops and tablets

Windows 10/11 or macOS 12+
Supported browsers:

- Google Chrome (recommended) and Microsoft Edge
- Not compatible with Safari, Samsung Internet, Firefox, or Opera



Connections and compatibility

Device connections

i-max, knob cylinder, i-minimal, i-volution, i-reader, i-gate: connection via PC to Lock cable + USB A to USB C adapter
i locker: direct connection via USB C cable
No wireless programming

Hardware compatibility

Compatible with TESA Hotel R3, R4, and R4n devices. (Not compatible with TESA Hotel devices older than R3, e.g. S6, S9)

TESA Hotel software compatibility

Requires TESA Hotel version 08.04.02 or higher
i-programmer functionality must be enabled in the TESA Hotel licence (factory enabled or added via software upgrade)



Security

TESA Hotel security architecture

Encrypted communications between mobile devices and TESA Hotel hardware
Firmware integrity validation before updates
Licence based authorization through TESA Hotel
Local data isolation: PC-To-Lock files remain stored on the device

TESA Hotel i-programmer

Installation, Operation, Setup

1. Installation

Installation on PC, laptop or tablet

Open a supported browser.

Visit:

<https://i-programmer.assaabloyibwebservices.com>

Install App to the desktop.

Installation on mobile phone

Scan QR code:

Install App on your Android



2. Operation

Once an installation is selected, the App enables you to connect to any TESA Hotel device and perform any of the following actions:

Info: device status, battery level, configuration, firmware version

Update: apply configuration updates

Events: retrieve stored event logs

Open: temporarily power and unlock device

Initialize: first time setup or reinitialization

Multitasking is not supported during operation.

Typical operation times (approx.):

Device initialization: 5-15 seconds

Event retrieval: 3-10 seconds (depending on volume)

Configuration update: 2-5 seconds

Firmware update: 30-90 seconds depending on device model

3. Setup

The Setup menu accesses advanced configuration tools:

Language selection (13 interface languages available): Catalan, Czech, Danish, German, English, Spanish, Basque, French, Italian, Dutch, Polish, Portuguese, Chinese

Firmware management: Update, verify and maintain device firmware

Advanced operations: Factory mode initialization, diagnostic log collection, technical support tools

Quick guide: A step-by-step guide is available to support app usage (available in English and Spanish)

Updates:

The App updates automatically when opened with Internet connection. Major updates may require:

- Clearing browser cache
- Reinstalling the App



ASSA ABLOY

© Images: All rights reserved by ASSA ABLOY.
We reserve the right to make technical modifications.
Version: TESA-Hotel_i-programmer_Datasheet_2026-05_EMEIA

TESA ASSA ABLOY
Talleres de Escoriaza, S.A.U.
Barrio Ventas, 35
20305 Irun · Gipuzkoa
Spain

Tel.: +34 943 669 100
www.tesa.es
www.assaabloy.com