

# Profile- double cylinder eCLIQ N531

Without key

**IKON**  
 ASSA ABLOY


## Product description



- Available as rotary secured or electronic version (V=)
- Other side can feature an electronic or rotary-secured design
- Brass cylinder housing components
- Standard finish, satin nickel-plated (OF=MV)
- Basic cylinder length 61 mm (C) - A/B (L=30/30) - other installation lengths available - flexible modular system
- Optional, differing basic cylinder length of 56 mm (C) - A/B (L=28/28)
- Standard locking cam position (SST=30°); differing locking bit position available, optionally available with SST=FLEX
- Optionally available with double locking cam (VAR=K901310-X-BIFFAR)
- Optional with SST=FZG possible
- Optionally available with anti drilling protection class 2 (AB=2)
- Both side locking (GE=BS) and 360° free-wheeling function as standard
- Cam made of break-proof, corrosion-resistant stainless steel
- Maintenance-free for up to 200,000 cycles
- Splash-proof IP54
- Dust and rain protection cap available for one or both sides (SUR=3/-, -/3, 3/3) IP55
- Optionally VdS (SZ=VDS-BZ+, AB=3)
- Optionally DIN EN 15684 with anti drilling protection class 2 (SZ=DIN, AB=2)
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (ATEX=II 2G EX IB IIB T4 Gb)

## Scope of delivery

- 1 profile-double cylinder
- 1 cylinder fixing screw M5 x 85 mm

## Variants that can be ordered

| Article number | OF=   | L=    | V=  |
|----------------|-------|-------|-----|
| N531           | MV/MV | 30/30 | D/D |
|                | MV/MV | 30/30 | E/D |
|                | MV/MV | 30/30 | D/E |
|                | MV/MV | 30/30 | E/E |



VAR=K901310-X-BIFFAR

