

Product description

Electric strike for horizontal panic door locks. Suitable for the surface-mounted casing ATP-----20105-01

Overview of Advantages

- Vertical and horizontal mounting possible
- Due to 180° fitting, can be used DIN right and left

Scope of delivery

- 1 piece electric strike

Technical data

Dimensions	Height: 112 mm , Width: 20.5 mm , Depth: 28 mm
Version	other
Latch version	other
Mounting	asymmetrical
Installation position	vertical
With fixing	No
Opening direction according to DIN	left/right
Waterproof	No
Mounting method	applied
How they work	Fail-locked
Pulse contact	Yes
Adjustable keeper- FaFix	No
Adjustable electric strike – Fix	No
Adjustable strike plate	No
Latch bolt guide integrated – Profix	No
For strike plates with latch bolt guide	No
Unlocking type	Standard version
Mechanical unlocking	No
Suitable for smoke protection door	No
Mechanical stability (no burglary resistance)	6500 N
Load cycles for in-plant test	250000
Changeable connection	No
Clampable/ plug-in connection	No
Mechanical noise damping	No
Drill hole offset by 1 mm	No
Unlock period	0.8 s
Operating temperature range	-15-40 °C
Certified in compliance with	EN 14846
Suitable for fire door	No
ATP	Yes
With feedback signal	No
Protective diode	No

Variants that can be ordered

Order number	Description
14.400-----D11	Without strike plate, 6-12 V AC/DC
14.400-----R11	Without face plate, 8-16 V AC/DC
14.400-----F11	Without face plate, 24 V AC/DC
14.400-----E31	Without striking plate, 12 V DC electric unlocking
14.400-----F31	Without striking plate, 24 V DC electric unlocking

