

Electric Strikes from effeff



Auxiliary locking model 9338


ASSA ABLOY

Concealed installation, flat surface

ASSA ABLOY, the global leader
in door opening solutions

Auxiliary locking model 9338

Concealed solution for higher tamper protection

The innovative auxiliary locking system 9338 is an elegant, universal solution.

It consists of a 138T ProFix® series electric strike and a magnetic bolt counterpart and is suitable for any area of additional locking elements. As a concealed solution, it offers higher tamper protection compared to conventional holding magnets.

The difference:
complete integration – flat surface

The additional locking element 9338 is completely concealed installed in the door leaf and its frame. Compared to standard additional locking elements, the magnetic deadbolt stays inside the housing till the door reach the correct position. This ensures completely flat surfaces with no mechanical elements protruding. The concealed design creates a nice door design.

Application areas

The additional locking element can be used wherever an additional lock is required alongside the main lock. Typical application areas are medical and law practices or hotels for example. Another application area is in all types of interlocks, such as connected bathrooms in hospitals or hatches in laboratories. Thanks to the concealed design the door element / frame can be easily cleaned and high hygienic standards can be fulfilled, such as those in medical facilities.

For use in:

- Medical practices
- Law practices
- Hotels
- Interlocks
- Wet cells
- Hatches in laboratories



Low installation depth and subsequent adjustment options

The newly developed magnetic bolt counterpart is significantly more compact than other solutions in the market. Thanks to its low installation depth, it is particularly suitable for modern and slimline doors. The concealed bolt allows ProFix®2 technology to be used in this type of lock, thus offering decisive advantages for the whole locking system. Thanks to the ProFix® design, there is no need for a latch profile edge on the frame or the striking plate. A flanged striking plate is no longer required. The electric strike is fully integrated into the closed door profile and the door seal surface remains completely intact. The bolt can also be adjusted to the door structure after installation. The bolt used is remarkably quiet thanks to its excellent slide properties and no lubrication is required.

Benefits at a glance:

- ProFix®2 function: concealed installation, visually attractive
- No need for big visible cutouts in the frame
- No latch profile edge required on the frame; flanged striking plates are no longer necessary
- No additional closing pressure needed
- Fail-unlocked, fail-locked and reversible hold- open versions are available
- Optional: monitoring contact and armature contact
- Electric strike and magnetic latch are adjustable due to FaFix®



The 9338 model series in brief



Complete set with striking plate (160x24x3mm)

Electric strike with protection diode.

		<div>Voltage</div> <div>12 V DC</div> <div>24 V DC</div>	<div>E9</div> <div>F9</div>
Item/feature	Order code		
Magnetic deadbolt with fail-unlocked strike 138TQ53 and stainless steel striking plate no. 34G	9 3 3 8 - - - 3 4 G 3 5 * * 1		



Complete set with striking plate (160x24x3mm)

Electric strike with monitoring contact and protection diode.

		Voltage 12 V DC 24 V DC	<div>E9 F9</div>
Item/feature	Order No.		
Magnetic deadbolt with fail-unlocked strike 138TQ63 and stainless steel striking plate no. 34G	9 3 3 8 R R - 3 4 G 3 5 * * 1		



Set without striking plate

For flexible use with effeff brand ProFix®2 striking plates. Electric strike with protection diode

		Voltage 12 V DC 24 V DC	<div>E9 F9</div>
Item/feature	Order No.		
Magnetic deadbolt with fail-unlocked strike 138TQ53	9 3 3 8 - - - - - * * 1		



Set without striking plate

For flexible use with effeff brand ProFix®2 striking plates. Electric strike with monitoring contact and protection diode.

	Voltage 12 V DC 24 V DC	<div>E9 F9</div>
Item/feature	Order code	
Magnetic deadbolt with fail-unlocked strike 138TQ63	9 3 3 8 R R - - - - - * * 1	



Magnetic deadbolt

For use in combination with electric strikes in the 118T/138T/148T series

Item/feature	Order No.
Magnetic deadbolt	9 3 3 8 - - - - - 0 0

Note:

Versions are also available with fail-locked strikes:
Model range **9318**.

Example:

Order code for a complete set, 10-24 V AC/DC
9318---34F35A71.

Please note:

The Magnetic deadbolt function will only work with electric strikes from the 138T, 118T and 148T series.

[More information at www.assaabloy.de/en/local/de/](http://www.assaabloy.de/en/local/de/)

ASSA ABLOY is the global
leader in door opening solutions,
dedicated to satisfying
end-user needs for security,
safety and convenience

ASSA ABLOY

ASSA ABLOY
Sicherheitstechnik GmbH

Bildstockstrasse 20
72458 Albstadt
Germany
Tel. +49 7431 123-700
Fax +49 7431 123-258
albstadt@assaabloy.com

www.assaabloy.de