Electric strike 27



Product description

Model with basic equipment.

Overview of Advantages

- Suitable for all common striking plates
- Due to 180° fitting, can be used DIN right and left
- Symmetrical design

Technical data

Dimensions	Height: 75 mm , Width: 20.5 mm , Depth: 28 mm
Version	Standard electric strikes
Latch version	Standard latch
Mounting	symmetrical
Installation position	universal
With fixing	Yes
With feedback signal	No
Opening direction according to DIN	left/right
Waterproof	No
Mounting method	Installation
How they work	Fail-locked
Pulse contact	Yes
Adjustable keeper- FaFix	Yes
Adjustable electric strike – Fix	No
Unlocking type	Standard version
Suitable for smoke protection door	No
Mechanical stability (no burglary resistance)	3500 N
Min. preload DC	10 N
Latch adjustment range	3 mm
Load cycles for in-plant test	250000
Changeable connection	No
Clampable/ plug-in connection	No
Protective diode	No
Mechanical noise damping	No
Drill hole offset by 1 mm	No
Unlock period	0.8 s
Operating temperature range	-15-40 °C
Certified in compliance with	EN 14846
Suitable for fire door	No
Mechanical unlocking	No

Variants that can be ordered

Order number	Description
27----------D11	Without strike plate, 6-12 V AC/DC
27----------R11	Without face plate, 8-16 V AC/DC
27----------F11	Without face plate, 24 V AC/DC
27----------E41	Without striking plate, 12V DC 100%ED
27----------F41	Without striking plate, 24V DC 100%ED

ASSA ABLOY Sicherheitstechnik GmbH
Bildstockstraße 20, 72458 Albstadt
Tel. + 49 7431/123-0, Albstadt@assaabloy.com
www.assaabloy.com/de