

## 4700LN SERIES

ANSI/BHMA Grade 1 Certified  
Cylindrical Lever Locks



# TABLE OF CONTENTS

## Contents

- [Features & Specifications.....](#)3
- [Finishes & How To Order.....](#)4
- [Lever Trim.....](#)5
- [Functions.....](#)6-8
- [Electrified Options.....](#)9
- [Electrified Accessories.....](#)10
- [Cylinders.....](#)11
- [Cylinders/Keying.....](#)12
- [Latchbolts.....](#)13
- [Strikes.....](#)14

## 4700LN Series Cylindrical Lever Locks

ASSA ABLOY ACCENTRA® 4700LN cylindrical locks are the ideal choice for a wide variety of commercial applications where consistent quality, ease of use and installation are required at an economical price. The 4700LN Series is certified to ANSI/BHMA Grade 1 standards and is UL fire-listed for all functions ensuring reliability and peace of mind.

 **WARNING**

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov).

## FEATURES & SPECIFICATIONS

### Features

- Available in 19 functions, 5 lever designs, and 9 finishes
- Knurled lever designs available
- Freewheeling trim
- Available with Microshield® antimicrobial coating



### Specifications


|                       |                                                                                                      |
|-----------------------|------------------------------------------------------------------------------------------------------|
| <b>Door Thickness</b> | 1-3/4" (44mm) to 2" (51mm); 1-3/8" (35mm) or 2-1/4" (57mm), please specify on order                  |
| <b>Strike</b>         | ANSI 4-7/8" x 1-1/4" x 1-1/4" (124mm x 32mm x 32mm) lip to center. See page 14 for optional strikes. |
| <b>Backset</b>        | 2-3/4" (70mm)                                                                                        |
| <b>Handing</b>        | Non-handed                                                                                           |
| <b>Installation</b>   | ANSI/SDI A250.14                                                                                     |
| <b>ANSI/BHMA</b>      | Certified ANSI/BHMA A156.2, Series 4000 Grade 1                                                      |
| <b>Warranty</b>       | 5 year                                                                                               |

### Applications and Listings

- UL – cUL listed for use on fire doors having a rating up to and including 3 hours
- Windstorm certified refer to local codes
- Meets accessibility guidelines for the Americans with Disabilities Act and the requirements of the Uniform Federal Accessibility Standards and ANSI 117.1

Note: Any retrofit or other field modification to a fire-rated opening can potentially impact the fire-rating of the opening, and ASSA ABLOY ACCENTRA® makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

## FINISHES

| ANSI/BHMA Code<br>Finish Description                                               |                                                                                    |                                                                                    |                                                                                      |                                                                                     |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>605</b><br>Bright Brass,<br>Clear Coated                                        | <b>606<sup>1</sup></b><br>Satin Brass,<br>Clear Coated                             | <b>612</b><br>Satin Bronze,<br>Clear Coated                                        | <b>613E</b><br>Dark Oxidized Satin<br>Bronze - equivalent                            | <b>619*</b><br>Satin Nickel Plated,<br>Clear Coated                                 |
|   |   |   |   |  |
| <b>625</b><br>Bright Chrome Plated                                                 | <b>626*<sup>1</sup></b><br>Satin Chrome Plated                                     | <b>BSP <sup>1</sup></b><br>Black Suede Powder Coat                                 | <b>WSP</b><br>White Suede Powder Coat                                                |                                                                                     |
|  |  |  |  |                                                                                     |

1. Cylinders provided in these finishes only.

Note: Dark Oxidized Satin Bronze, Oil Rubbed (613) and Black Oxidized Bronze, Oil Rubbed (722) finishes are available by Special Product Application Request only. Contact customer service for more information.

\*Finish available with MicroShield® antimicrobial coating, additional finishes by special application. Consult factory for availability.

MicroShield coating may vary finish color from architectural standards. MicroShield is not intended as a substitute for traditional infection control programs such as hand hygiene or use of disinfectants. Coated products must still be cleaned to ensure the surfaces will be free of destructive microbes. ASSA ABLOY ACCENTRA® makes no representations or warranties, express or implied, as to the efficacy of MicroShield.

## How To Order

| Trim Design | Function      | Hand       | Latch       | Strike      | Cylinder        | Door Thickness | Finish     |
|-------------|---------------|------------|-------------|-------------|-----------------|----------------|------------|
| See page 8  | See pages 5-7 | See page 3 | See page 13 | See page 14 | See pages 11-12 | See page 3     | See page 4 |

## Ordering Example



| Trim Design | Function | Hand | Latch | Strike | Cylinder | Door Thickness | Finish |
|-------------|----------|------|-------|--------|----------|----------------|--------|
| AU          | 4707LN   | RH   | 694   | 497    | 1803-47L | 1-3/4"         | 626    |

## LEVER TRIM

### Augusta AU

**Lever:** Cast Zinc


**Rose:** Wrought Brass



### Monroe MO

**Lever:** Cast Zinc


**Rose:** Wrought Brass



### Pacific Beach PB

**Lever:** Cast Zinc


**Rose:** Wrought Brass



### TB

**Lever:** Cast Zinc


**Rose:** Wrought Brass



### UB

**Lever:** Cast Zinc









**Rose:** Wrought Brass



Available with large and small format interchangeable core. See page 11-12 for details.









Dimensions shown are in inches (mm).

## FUNCTIONS

| 4701LN (F75)                                                                                                                                                                                                                                                                                                                                                                                                             | 4702LN (F76A)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 4703LN (F77A)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 4704LN (F82A)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Passage or Closet Latch</b> <ul style="list-style-type: none"> <li>For doors that do not require locking.</li> <li>Either lever operates latchbolt at all times.</li> </ul>  <p>Outside    Inside</p>                                                                                                                               | <b>Privacy, Bedroom or Bath Lock</b> <ul style="list-style-type: none"> <li>For lavatory or other privacy doors.</li> <li>Either lever operates latchbolt unless outside lever is locked by pushbutton inside.*</li> <li>Button automatically releases when inside lever is turned or door is closed.</li> <li>Emergency key inserted and turned in hole in outside lever will unlock door from outside. (Emergency key furnished with lockset. P/N 14-5302-1053-048)</li> <li>Inside lever always active.</li> </ul>  <p>Outside    Inside</p> | <b>Patio or Privacy Lock</b> <ul style="list-style-type: none"> <li>For exit doors with limited entry.</li> <li>Deadlocking latchbolt.</li> <li>Either lever operates latchbolt unless outside lever is locked by pushbutton inside.*</li> <li>Button automatically releases when inside lever is turned or door is closed.</li> <li>Inside lever always active.</li> </ul>  <p>Outside    Inside</p>                                                                                                                                                                                                                                                                                                                                                                                  | <b>Entry Lock</b> <ul style="list-style-type: none"> <li>For entrance or office doors.</li> <li>Deadlocking latchbolt.</li> <li>Either lever operates latchbolt (except when outside lever is locked from inside).*</li> <li>Pushing button in inside lever locks outside lever. (Automatically releases when inside lever is turned or key is rotated in locked outside lever.)</li> <li>Latchbolt is operated by key in outside lever or by rotating inside lever.</li> <li>Inside lever always active.</li> </ul>  <p>Outside    Inside</p> |
| 4705LN (F86)                                                                                                                                                                                                                                                                                                                                                                                                             | 4706LN (F92)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 4707LN (F109)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 4708LN (F84)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Storeroom or Closet Lock</b> <ul style="list-style-type: none"> <li>For use on storeroom, utility, exit doors.</li> <li>Deadlocking latchbolt.</li> <li>Latchbolt operated by lever inside, key in outside lever.</li> <li>Outside lever always locked.*</li> <li>Inside lever always active.</li> </ul>  <p>Outside    Inside</p> | <b>Service Station Lock</b> <ul style="list-style-type: none"> <li>Deadlocking latchbolt.</li> <li>Either lever operates latchbolt.</li> <li>Pushbutton in inside lever locks outside lever. (Automatically releases when inside lever is turned, door is closed or key is rotated in outside lever, except when slotted pushbutton is rotated 90° clockwise to retain outside lever in locked position.)*</li> <li>Latchbolt operated by key in outside lever, inside lever always active.</li> </ul>  <p>Outside    Inside</p>               | <b>Entry Lock</b> <ul style="list-style-type: none"> <li>For entrance, general home or office doors.</li> <li>Deadlocking latchbolt.</li> <li>Either lever operates latchbolt (except when outside lever is locked from inside).*</li> <li>Pushing turn button in inside lever locks outside lever. (Automatically releases when inside lever is turned or key is rotated in locked outside lever.)</li> <li>Outside lever may be retained in locked position by pushing and rotating turn button 90° clockwise to a horizontal position; not released until turn button is manually returned to the vertical position.</li> <li>Latchbolt is operated by key in outside lever or by rotating inside lever.</li> <li>Inside lever always active.</li> </ul>  <p>Outside    Inside</p> | <b>Classroom Lock</b> <ul style="list-style-type: none"> <li>For classroom or utility room doors.</li> <li>Deadlocking latchbolt.</li> <li>Either lever operates latchbolt (except when outside lever is locked by key).*</li> <li>Inside lever always active.</li> <li>Key releases outside lever.</li> </ul>  <p>Outside    Inside</p>                                                                                                                                                                                                      |



\* Lever handles are Free-Wheeling in locked position. Shaded area denotes FreeWheeling lever.

## FUNCTIONS

| 4709LN (F89)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 4718LN (F110)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 4721LN (F80)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 4722LN (F90)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Exit Latch</b> <ul style="list-style-type: none"> <li>For exit doors with no-entry desired.</li> <li>Deadlocking latchbolt.</li> <li>Outside lever always locked.*</li> <li>Inside lever always active.</li> </ul>  <p>Outside    Inside</p>                                                                                                                                                                                                                                                                                  | <b>Intruder Classroom Lock</b> <ul style="list-style-type: none"> <li>For classroom doors.</li> <li>Deadlocking latchbolt.</li> <li>Either lever operates latchbolt (except when outside lever is locked by key from either side).</li> <li>Outside lever remains locked upon egress</li> <li>Inside lever always active.</li> </ul> <b>(NOTE: Not available with I.C. core cylinders.)</b>  <p>Outside    Inside</p>  | <b>Communicating Lock</b> <ul style="list-style-type: none"> <li>For communicating or store entrance doors.</li> <li>Deadlocking latchbolt.</li> <li>Either lever operates latchbolt (except when key in either lever locks or unlocks the lever independently of the other).*</li> <li>Should be used only in offices or rooms with multiple entries.</li> </ul> <b>(NOTE: Not available with I.C. core cylinders.)</b>  <p>Outside    Inside</p>                                              | <b>Corridor Lock</b> <ul style="list-style-type: none"> <li>Deadlocking latchbolt.</li> <li>Either lever operates latchbolt (except when outside lever is locked by inside push-button or key in outside lever). Inside lever always active.</li> <li>When locked by button, the button automatically releases when inside lever is turned or door is closed.</li> <li>When locked by key, the automatic release is made inoperative and must be manually unlocked by key.</li> </ul>  <p>Outside    Inside</p> |
| 4725LN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 4728LN (F111)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 4729LN (F113)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 4730LN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Privacy Lock</b> <ul style="list-style-type: none"> <li>For lavatory or other privacy doors.</li> <li>Either lever operates latchbolt (except when outside lever is locked by inside pushbutton).*</li> <li>Button automatically releases by turning inside lever or closing door.</li> <li>Door can be unlocked, when necessary, by operating outside turnbutton.</li> <li>No emergency key required.</li> <li>Optional flush turnbutton available for outside. Specify option "FTB".</li> </ul>  <p>Outside    Inside</p> | <b>Communicating Passage Lock</b> <ul style="list-style-type: none"> <li>For twin communicating or exit doors where one side operation is required.</li> <li>Also when space is limited between door and switch panel.</li> <li>Deadlocking latchbolt.</li> <li>One lever operation.</li> <li>Blank rose.</li> <li>Should be used only where rooms have more than one entrance.</li> </ul>  <p>Outside    Inside</p> | <b>Communicating Classroom Lock</b> <ul style="list-style-type: none"> <li>For twin communicating or closet doors where one side operation is required or space between doors is limited.</li> <li>Deadlocking latchbolt.</li> <li>Inside lever operates latchbolt except when lever is locked by key.*</li> <li>Blank rose.</li> <li>Should be used only where rooms have more than one entrance.</li> </ul> <b>(NOTE: Not available with I.C. core cylinders)</b>  <p>Outside    Inside</p> | <b>Utility, Asylum or Institutional Lock</b> <ul style="list-style-type: none"> <li>Deadlocking latchbolt.</li> <li>Latchbolt operated by key in lever from either side.</li> <li>Both levers always locked.*</li> </ul> <b>Note: Not available with IC core cylinders.</b>  <p>Outside    Inside</p>                                                                                                                                                                                                         |

\* Lever handles are Free-Wheeling in locked position. Shaded area denotes FreeWheeling lever.

## FUNCTIONS

| 4739LN (F112)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 4755LN                                                                                                                                                                                                                                                                        | 4755LN-D                                                                                                                                                                                                                                                                          |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>Communicating Storeroom Lock</b></p> <ul style="list-style-type: none"> <li>• For twin communicating or closet doors where one side operation is required or space between doors is limited.</li> <li>• Deadlocking latchbolt.</li> <li>• Latchbolt operated by key only in inside lever.</li> <li>• Inside lever always locked.*</li> <li>• Blank rose.</li> <li>• Should be used only where rooms have more than one entrance.</li> </ul> <p><b>(Note: Not available with I.C. core cylinders)</b></p>  <p>Outside      Inside</p> | <p><b>Single Dummy Trim</b></p> <ul style="list-style-type: none"> <li>• For non-operational levers used for decorative trim.</li> <li>• Rigid lever.</li> </ul>  <p>Outside      Inside</p> | <p><b>Double Dummy Trim</b></p> <ul style="list-style-type: none"> <li>• For non-operational lever used for decorative trim.</li> <li>• Through-bolted.</li> </ul>  <p>Outside      Inside</p> |

\* Lever handles are Free-Wheeling in locked position. Shaded area denotes FreeWheeling lever.

## ELECTRIFIED OPTIONS

### Operation

Electric locks provide the ability to electrically lock or unlock the outside trim from a remote location. Fail Safe locks are commonly used in stair towers to release upon fire alarm activation. Fail Secure locks are used on perimeter doors or security doors to allow ingress using access control technologies (proximity cards, keypads, etc.)



### Features

- Free Wheeling lever mechanism.
- Self-contained, continuous-duty integral solenoid (allows installation in standard cylindrical prep).
- Available Fail Safe or Fail Secure.
- Available in 12 or 24 volts DC.
- External rectifier available upon request for AC operation.
- Mechanical cylinder override.
- All 4700LN cylinder options.
- Certified ANSI/BHMA Grade 1. 
- UL listed.
- 1-year limited warranty.


### Electrical Specifications

- Continuous duty solenoid  
150 mA @ 24VDC  
300 mA @ 12VDC



### ElectroLynx®



Electrified 4700LN locks are equipped with ElectroLynx connectors. As a standard feature, these connectors link power from the incoming source to electrified locking products, including hinges, locks, exit devices, magnetic holders and strikes.

**Note:** Electrified door hardware with ElectroLynx connectors requires a compatible number of lead wires attached to the door hinge.



### Functions

| Outside                                                                             | Inside | Function | Function Description                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------|--------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |        | 4790LN   | <b>Fail Safe</b> <ul style="list-style-type: none"> <li>• Deadlocking latchbolt by lever either side except when power on locks outside lever.</li> <li>• Power off/unlocks outside lever.</li> <li>• Inside lever always free.</li> <li>• Latchbolt retracted by key when power is on.</li> </ul>    |
|  |        | 4791LN   | <b>Fail Secure</b> <ul style="list-style-type: none"> <li>• Deadlocking latchbolt by lever either side except when power off locks outside lever.</li> <li>• Power on/unlocks outside lever.</li> <li>• Inside lever always free.</li> <li>• Latchbolt retracted by key when power is off.</li> </ul> |

| Outside                                                                              | Inside | Function | Function Description                                                                                                                                                                                                                         |
|--------------------------------------------------------------------------------------|--------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |        | 4780LN   | <b>Fail Safe</b> <ul style="list-style-type: none"> <li>• Deadlocking latchbolt by lever either side except when power on locks outside lever.</li> <li>• Power off/unlocks outside lever.</li> <li>• Inside lever always free.</li> </ul>   |
|  |        | 4781LN   | <b>Fail Secure</b> <ul style="list-style-type: none"> <li>• Deadlocking latchbolt by lever either side except when power off locks outside lever.</li> <li>• Power on/unlocks outside lever.</li> <li>• Inside lever always free.</li> </ul> |

## ELECTRIFIED OPTIONS

### LSP-12-24 POWER SUPPLY

#### Operation

LifeSafety Power supplies are designed to provide reliable filtered and regulated power for long life to a variety of electrified hardware components.

#### Features

- Selectable voltage output between 12V and 24V with a single switch
- Internal Back-Up battery charging circuit \*
- Regulated and filtered, fuse protected outputs
- Each output can be individually turned on and off via a jumper
- Power status of each output is shown by an LED
- Rugged steel enclosure
- Fire alarm interface included – Dry contacts NO/NC, 9-33VDC, 3-15mA

#### Electrical Specifications

- Inputs: 120VAC
- Outputs: 12VDC @ 6 Amp or 24VDC @3 Amp
  - 8 Total Outputs

#### Listings

- UL294, UL603, UL1076
- ULC S318, ULC S319

#### Applications

- Fail safe cylindrical locks
- Fail secure cylindrical locks

\* Note: Batteries are not included with the power supply



| Model     | Description                          |
|-----------|--------------------------------------|
| LSP-12-24 | 12V – 6AMP / 24V – 3AMP Power Supply |



ASSA ABLOY ACCENTRA® recommends McKinney®, Pemko and Securitron® for power transfer devices and other electronic accessories.

## CYLINDERS

### Cylinder Options

The following selection guide indicates the correct cylinder for each locking segment.

| Lockset Series:<br>4700LN |                      | Types of Cylinder Mechanisms |       |                  |       |           |       |
|---------------------------|----------------------|------------------------------|-------|------------------|-------|-----------|-------|
|                           |                      | Conventional                 |       | Protected Keyway |       | Security  |       |
| Cylinder Types            | Fixed Core           | 6-pin                        | 7-pin | 6-pin            | 7-pin | 6-pin     | 7-pin |
|                           | Key-In-Lever         | 1803-47L*                    | N/A   | K403-47L*        | N/A   | 5803-47L* | N/A   |
|                           | Interchangeable Core |                              |       |                  |       |           |       |
|                           | LFIC                 | 1210                         | N/A   | K800             | N/A   | 5210      | N/A   |
|                           | SFIC                 | A600                         | A600  | K600             | K600  | N/A       | N/A   |




**Cylinder Sleeve\***  
P/N 14-1803-9001-999

Refer to ASSA ABLOY ACCENTRA® KeyMark® and/or Cylinders and Keys Catalog sections for all details and how-to-order examples.

\*Cylinders require cylinder sleeve P/N 14-1803-9001-999 to fit locksets manufactured prior to January 2022.

### ASSA ABLOY ACCENTRA® KeyMark®


For those applications requiring protected key control, ASSA ABLOY ACCENTRA® KeyMark® cylinders guard against unauthorized key duplication. The ASSA ABLOY ACCENTRA® KeyMark® Security Leg® keyway feature increases resistance against picking and impressioning and can easily retrofit into existing systems. For further details and availability, refer to the separate ASSA ABLOY ACCENTRA® KeyMark® catalog.



### Security Cylinders

Security cylinders contain two independent locking mechanisms. The first is a traditional 6-pin tumbler mechanism with spool drivers for greatly increased picking resistance.

The second is an innovative 5-tumbler rotating disc mechanism with sidebar engagement. The rotating discs are spring loaded and block the bottom of the keyway.




### 108S Schlage® Cylinder Adapter Kit

Kit used to modify Schlage® cylinder for fit in the 4700LN.


P/N 14-5305-0090-048 - 108S

Kit includes tailpiece and sleeve. To order the 108S adapter kit with the lock, use an "S" prefix (i.e., S-AU4707LN).



## CYLINDERS/KEYING

### Other Manufacturer Keyway Cylinder/Cores

| Illustration                                                                                               | Description                                                                                                                    | Lever         | Number of Pins      |
|------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|---------------|---------------------|
|                           | Best® Keyway Core.<br>Available keyed random, master keyed or uncombined. Specify keyway A, B, C, D, E, F, G, H, J, K, L or M. | A600          | 6 or 7<br>(Specify) |
| <br><b>Lever Cylinder</b> | Schlage® C Keyway Cylinder.<br>Available 0-bitted or keyed random.                                                             | 2803-47L x C  | 6                   |
|                                                                                                            | Corbin Russwin L4 Keyway Cylinder.<br>Available keyed random.                                                                  | 3803-47L x L4 | 6                   |
|                                                                                                            | Corbin 60 Keyway Cylinder.<br>Available keyed random.                                                                          | 3803-47L x 60 | 6                   |
|                                                                                                            | Russwin D1 Keyway Cylinder.<br>Available keyed random.                                                                         | 3803-47L x D1 | 6                   |
|                                                                                                            | Sargent® LA Keyway Cylinder.<br>Available keyed random.                                                                        | 3803-47L x LA | 6                   |
|                                                                                                            | Schlage® E Keyway Cylinder.<br>Available keyed random.                                                                         | 3803-47L x E  | 6                   |

Notes: The 2803 and 3803 cylinders require a cylinder sleeve (P/N 14-1803-9001-999) to fit 4700LN locksets manufactured prior to January 2022.

### Levers Accepting SFIC And Other Manufacturers' Large Format Interchangeable Cores

| Illustration                                                                        | Description                                           | Prefix                                | Number of Pins |
|-------------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------|----------------|
|  | SFIC (Accepts all Small Format Interchangeable Cores) | B (i.e. B-AU, B-MO, B-PB, B-TB, B-UB) | 6 or 7         |
|  | Medeco®, ASSA® (LFIC)                                 | M*<br>(i.e. M-AU)                     | 6              |
|                                                                                     | Schlage® (LFIC)                                       | SI<br>(i.e. SI-AU, SI-PB)             | 6              |

\*Medeco®, ASSA® option available only with AU lever. (Note: For Medeco 32 series cores.)

LFIC = Large Format Interchangeable Core

SFIC = Small Format Interchangeable Core


### Levers Accepting Other Manufacturers' Fixed Core Cylinders

| Illustration                                                                        | Description | Prefix                       | Number of Pins |
|-------------------------------------------------------------------------------------|-------------|------------------------------|----------------|
|  | Schlage®    | S<br>(i.e. S-AU, S-MO, S-PB) | 6              |

## LATCHBOLTS

### Plain Latchbolts

Model No. 693 supplied standard with all 4700LN series locksets without locking function. Standard plain latchbolt has a 2-1/4" (57mm) x 1-1/8" (29mm) beveled front with a 2-3/4" (70mm) backset and a 1/2" (13mm) bolt throw. Optional latchbolts with a greater backset/throw available to special order.




| Model No. | Front   | Backset       | Throw       | Front Width   | Latch Diameter |
|-----------|---------|---------------|-------------|---------------|----------------|
| 693       | Beveled | 2-3/4" (70mm) | 1/2" (13mm) | 1-1/8" (29mm) | 1" (25mm)      |
| F693      | Flat    | 2-3/4" (70mm) | 1/2" (13mm) | 1-1/8" (29mm) | 1" (25mm)      |
| 3693      | Beveled | 3-3/4" (95mm) | 1/2" (13mm) | 1-1/8" (29mm) | 1" (25mm)      |

**Note: for 3/4" throw applications, only deadlocking latchbolts available.**

### Deadlocking Latchbolts

Deadlocking latchbolt Model No. 694 supplied standard with all 4700LN series locksets with mechanical locking function. E694 is the standard latch provided for electrified functions. Standard deadlocking latchbolt has a 2-1/4" (57mm) x 1-1/8" (29mm) universal front with a 2-3/4" (70mm) backset and a 1/2" (13mm) bolt throw. Optional latchbolts with a greater backset/throw available to special order.



| Model No. | Front      | Backset       | Throw       | Front Width   | Latch Diameter |
|-----------|------------|---------------|-------------|---------------|----------------|
| 694       | Adjustable | 2-3/4" (70mm) | 1/2" (13mm) | 1-1/8" (29mm) | 1" (25mm)      |
| E694      | Adjustable | 2-3/4" (70mm) | 1/2" (13mm) | 1-1/8" (29mm) | 1" (25mm)      |
| 3694      | Beveled    | 3-3/4" (95mm) | 1/2" (13mm) | 1-1/8" (29mm) | 1" (25mm)      |
| 480B      | Beveled    | 2-3/4" (70mm) | 3/4" (19mm) | 1-1/8" (29mm) | 1" (25mm)      |
| F480B     | Flat       | 2-3/4" (70mm) | 3/4" (19mm) | 1-1/8" (29mm) | 1" (25mm)      |
| 3480B     | Beveled    | 3-3/4" (95mm) | 3/4" (19mm) | 1-1/8" (29mm) | 1" (25mm)      |


**Note: for 2-3/8" backset, contact Customer Support.**

### Backset Extension Links

All 4700LN Series locksets are supplied with standard latchbolts of 2-3/4" (70mm) backset; optional latchbolts with a 3-3/4" (95mm) backset are available to special order for lever locksets only. Extension links are also available for attachment to 2-3/4" (70mm) or 3-3/4" (95mm) backset latchbolts to extend the backset to the desired length.

| Desired Backset | Latchbolt Backset | Order Extension List No. |
|-----------------|-------------------|--------------------------|
| 5" (127mm)      | 2-3/4" (70mm)     | 481DL                    |
| 6" (152mm)      | 3-3/4" (95mm)     | 481                      |
| 7" (178mm)      | 2-3/4" (70mm)     | 482                      |
| 8" (203mm)      | 3-3/4" (95mm)     | 482                      |
| 18" (46cm)      | 2-3/4" (70mm)     | 484                      |
| 19" (48cm)      | 3-3/4" (95mm)     | 484                      |

**Other extension links up to 42" (1.06m) backset are available to special order.**



### Attaching Screws

(Not regularly supplied when latchbolts ordered separately).

#### • For all latchbolts

#8-32 x 3/4" (19mm) Phillips flat head combination wood and machine screws  
Brass - P/N 81-2022-0416\*  
Bronze - P/N 81-2032-0416\*




#### • Hollow Metal Doors

#8-32 x 1" (25mm) Phillips flat head machine screw  
Brass - P/N 81-0022-0420\*  
Bronze - P/N 81-0032-0420\*

\*Specify finish required.

## STRIKES

4700LN locks are available with a variety of strike options. All strikes are located on the same vertical and horizontal center lines as the latchbolt. Some strikes are available in a variety of lip lengths to accommodate varying thickness of doors and frames. To determine the proper length of the lip, measure from the center line of the strike to the edge of the jamb, accounting for any interfering trim (i.e. wood molding) and then add 1/4" (6mm) for curved lip. All strikes are reversible. Strikes are fabricated of either brass, bronze or stainless steel, depending on the lockset trim finish. When ordering strikes separately, specify the finish required.

|                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                               |                                                                                                      |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                                                                                 |                                                                                                                                                              |                   |
| <p><b>Model No. 497 ANSI Strike (Standard)</b><br/>For door and frames with ANSI preparations. 4-7/8" x 1-1/4" x 1-1/4" (124mm x 32mm x 32mm) lip to center supplied standard. 1-1/8", 1-1/2", and 1-3/4" lip lengths available by special order. Available with optional 202 Strike Box. Specify 497 x 202.</p> | <p><b>Model No. 371 T-Strike (Optional)</b><br/>2-3/4" x 1-1/8" x 1-1/4" (70mm x 29mm x 32mm) lip to center available as an option. 1", 1-1/2", 1-3/4" and 2" curved lip lengths available by special order. Wrought strike box supplied.</p> | <p><b>Model No. 202 Strike Box (Optional)</b><br/>Available to special order. Specify 497 x 202.</p> |

## Attaching Screws

(Not regularly supplied when strikes ordered separately).

### For Model No. 497

#12-24 x 1" Phillips flat head combination wood and machine screws.  
P/N 81-2012-0620

### For Model No. 371

#8-32 x 3/4" (19mm) Phillips flat head combination wood and machine screws.  
P/N 81-2012-0416

## NOTES

The ASSA ABLOY Group is the global leader in access solutions.  
Every day, we help billions of people experience a more open world.

ASSA ABLOY Opening Solutions leads the development within door openings and products for access solutions in homes, businesses and institutions. Our offering includes doors, frames, door and window hardware, mechanical and smart locks, access control and service.

**ACCENTRA®**  
**ASSA ABLOY**

#### **TECHNICAL SUPPORT**

(troubleshooting, product use and application, returns)

Tel: 855-557-5078

Email: [techsupport.accentra@assaabloy.com](mailto:techsupport.accentra@assaabloy.com)

#### **CUSTOMER SUPPORT**

(orders, product configuration, pricing, lead-time)

Tel: 855-557-5078 x2

Email: [Customerservice.Accentra@assaabloy.com](mailto:Customerservice.Accentra@assaabloy.com)

**U.S.A.:**  
**ASSA ABLOY ACCENTRA®**  
225 Episcopal Road  
Berlin, CT 06037-4004  
Tel: 1-800-438-1951  
Fax: 1-800-338-0965  
[www.accentra-assaabloy.com](http://www.accentra-assaabloy.com)

**Canada:**  
**ASSA ABLOY Door Security Solutions Canada**  
160 Four Valley Drive  
Vaughan, Ontario L4K 4T9  
Tel: 1-800-461-3007  
Fax: 1-800-461-8989  
[assaabloydss.ca](http://assaabloydss.ca)

**International:**  
**ASSA ABLOY Americas International**  
Tel: 1-905-821-7775  
Fax: 1-905-821-1429  
[assaabloyai.com](http://assaabloyai.com)