

1. Unique identification code of the product-type:

Brand	ASSA ABLOY
Model(s)	Twin Bolt Lock, 14mm, 18mm throw, with and without door furniture, locking and non locking options
Part Number / identifier	Twin Bolt Lock
Bar code	-
Description/Type	Twin Bolt Lock with and without door furniture
Production type	Batch or mass-produced products
NZ Building Product class	Class 1

2. Product description and its intended use(s)

Twin Bolt lock in 14mm and 18mm throw options, with and without furniture. Locking and non locking options. Suitable for use with aluminium or uPVC hinged windows and doors.

Key Features:

- Designed for handles with standard spindle
- Internal locking only
- Provides two points of security with throw rods top and bottom
- Standard rod length 1m + 1.3m available (not included)
- 18mm throw on rods
- Practical, easy installation
- Zinc die-cast construction
- Standard moulded plastic packers and fixing screws provided
- Threaded rod connection provides easy adjustment
- Wafer cylinder with Euro escutcheon cover
- Can be keyed alike to other ASSA ABLOY CYL4™ locks for one key convenience
- Supplied in trade pack
- New Zealand made

Applications:

- Bi-folding doors and windows.

3. Place of Manufacture:

Place of Manufacture

- Aotearoa New Zealand Overseas, see manufacturer section for details

Generic Model: Twin Point Lock

Type: Bifold Hinge Door Lock

4. Legal and trading name of the manufacturer(s):

ASSA ABLOY Australia Pty Ltd.

Address for Service

Street name and number	6 Armstrong Road
Suburb	Albany
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	https://www.assaabloy.com/nz/en
Email	nzsales@assaabloy.com
Phone	+64 (0) 9 448 9188
Business number	NZBN: 9429036762194

5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd

Address for Service

Street name and number	
Suburb	
Region/state	
Country	
Post code	
Website	
Email	
Phone	
Business number	

6. Relevant Building Code clauses:

Standard	Clause(s)
Building Regulations 1992	B2.3.1 – Durability; Performance
Building Regulations 1992	D1 – Access routes D1.3.1(b), D1.3.4(f)

Generic Model: Twin Point Lock

Type: Bifold Hinge Door Lock

7. Statement on how the building product is expected to contribute to compliance.

The Twin Bolt Bifold range of hardware allows for secondary access for accessible routes.

8. Limitations on the use of the building product:

- The Twin Bolt lock is not fire rated and is designed to be used for residential use.
- Refer to the installation instructions for correct fitment

9. Design requirements that would support the appropriate use of the building product.

Must be installed as per instructions

10. Installation requirements

- Refer to the installation instructions available
- [RES_FLY_044_Twin_Bolt_Bifold_Flyer.pdf \(assaabloyopeningsolutions.nz\)](#)
- [077088_Twin_Bolt_Lock_Bifold_Doors_with_Furniture_Installation_Instructions.pdf \(assaabloyopeningsolutions.nz\)](#)

11. Maintenance requirements

- Clean the external surfaces with a dry cloth only, do not use chemicals.
- Door alignment and maintenance is essential to maintain locking alignment and performance.

12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

Yes No

If yes, description of the warning or ban under section 26

N/A

13. Date

Date of document completion (day/month/year)

2	1	1	1	2	0	2	3
---	---	---	---	---	---	---	---