

1. Unique identification code of the product-type:

Brand	Lockwood
Model(s)	530-930 Series
Part Number / identifier	530-930 Series
Bar code	-
Description/Type	Key N Knob
Production type	Batch or mass-produced products
NZ Building Product class	Class 1

2. Product description and its intended use(s)

Key Features:

- Entrance Sets: Operated by key from outside and turnsnib from inside
- Privacy Sets: Operated by turnsnib inside with outside emergency release
- Passage Sets: Outside and inside knob/lever always free
- Glass Sets: Operated by key from outside and key from inside
- Can be keyed alike, master keyed, grand master keyed, maison keyed or construction keyed
- Lever and Roses High purity zinc alloy
- Standard deadlatch backset of 70mm
- Latch is 13mm projection brass bolt
- Cylinder is a 5 pin tumbler mechanism with brass cylinder and brass barrel
- Non-handed lockset

Applications:

- Suits door thickness of 32 to 48mm (all functions except 534 which suits doors 32 to 45mm)

3. Place of Manufacture:

Place of Manufacture

Aotearoa New Zealand

Overseas, see manufacturer section for details

4. Legal and trading name of the manufacturer(s):

ASSA ABLOY Australia Pty Ltd.

Address for Service

Street name and number	235 Huntingdale Road
Suburb	Oakleigh
Region/state	Victoria
Country	Australia
Post code	3166
Website	https://www.assaabloy.com.au/
Email	https://www.assaabloy.com/au/en/contact-us
Phone	+61 3 8574 3619
Business number	ABN: 90 086 451 907

5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd.

Address for Service

Street name and number	6 Armstrong Road
Suburb	Albany
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	https://www.assaabloy.com/nz/en
Email	nzsales@assaabloy.com
Phone	+64 (0) 9 448 9188
Business number	NZBN: 9429036762194

6. Relevant Building Code clauses:

Standard	Clause(s)
Building Regulations 1992	B2.3.1 – Durability; Performance
Building Regulations 1992	D1 – Access routes D1.3.1 (b), D1.3.2 (b)
Building Regulations 1992	C3.3 – Fire affecting areas beyond the fire source
Building Regulations 1992	C4.2 – Movement to a place of safety

7. Statement on how the building product is expected to contribute to compliance.

- B2.3.1(c) (i) and (ii): Successfully tested to confirm with Level D8 (500,000) cycles under Australian Standard AS4145.2-2008, locksets and hardware for doors and windows.
- C3.3 and C4.2: Successfully tested up to 2 hours with a fire rated Lockwood mortice lock on fire door assemblies (depending on type of doorset) in accordance with Australian Standard AS1905.1, Fire Resistant Doorsets.
- D1.3.1 and D1.3.2 (b): Series includes levers and turns that meet the requirements of AS1428.1-2009, Design for access and mobility. Refer to the specifications for compliant models.

8. Limitations on the use of the building product:

- Refer to the installation instructions for correct fitment

9. Design requirements that would support the appropriate use of the building product.

Must be installed as per instructions

10. Installation requirements

- Refer to the installation instructions available online https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/930_and_950_Series_Key_in_Lever_Install

11. Maintenance requirements

- Door alignment and maintenance is essential to maintain locking alignment and performance.

12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

Yes No

If yes, description of the warning or ban under section 26

N/A

13. Date

Date of document completion (day/month/year)

0	1	1	0	2	0	2	3
---	---	---	---	---	---	---	---