1. Unique identification code of the product-type:

Brand	Lockwood
Model(s)	214 Series
Part Number / identifier	See table below
Bar code	N/A
Description/Type	Door furniture – 10mm Radius Corner Push/Pull Plates
Production type	Batch or mass-produced products
NZ Building Product class	Class 1

Brand	Lockwood
Model(s)	215 Series
Part Number / identifier	See table below
Bar code	N/A
Description/Type	Door furniture – 10mm Radius Corner Push/Pull Plates
Production type	Batch or mass-produced products
NZ Building Product class	Class 1

Note: There are too many combinations to legibly notate all the models and options, please refer to the chart below for the details.

ASSA ABLOY
Experience a safer and more open world

Ordering Procedure

Sample part number 21825NA/P2LSS is made up of several sections.
Choose your product by selecting an option from each section.

2000 Series

Plate Type	Plate Function	Engraving	Cylinder Shape	Handle	Handing	Finish
218	25	N	A /	P2	–	SS

Plate Type

Exterior Plate (300 x 100) – Radius Corners	214
Interior Plate (300 x 100) – Radius Corners	215
Exterior Plate (300 x 65) – Radius Corners	216
Interior Plate (300 x 65) – Radius Corners	217
Exterior Plate (250 x 50) – Radius Corners	218
Interior Plate (250 x 50) – Radius Corners	219

Plate Function

Cylinder Only	00
Emergency Turn Only	02
Turn Knob Only	06
Plain Plate	07
Privacy Indicator Emergency Turn Only	13
Pull Handle Only	24
Pull Handle and Cylinder	25
Pull Handle and Emergency Turn	26
Pull Handle and Turn Knob	27
Pull Handle and Privacy Indicator Emergency Turn	28
Disabled Turn Only - Synergy	38
Pull Handle and Disabled Turn Only - Synergy	42
Pull handle only - offset from bottom	44

Engraving

A – G Outlined Infill
R – X Full Infill

Male Symbol	A	R
Male Text	B	S
Female Symbol	C	T
Female Text	D	U
Disabled Symbol	E	V
Push Text	F	W
Pull Text	G	X
Unisex Symbol	H	Y
No Option	N	
Miscellaneous Text	P*^~	
Corporate Image	Q*^~	

*Line drawing of artwork in desired size must be specified on order.
^Desired location of engraving measured from the top left corner of plate must be specified on order.
~ Infill or Outline of engraving must be specified on order.

Cylinder Shape

Oval Cylinder – 32mm (H) x 18mm (W) Lockwood 570 Cylinders	A
No Cylinder Function	N

Lever/ Knob Type

Brass Pull Handles

P1	P2	P3
P4		

Handing

Left Handed	L
Right Handed	R

* Note 2 - Not all handles are available with each function, please refer to the function chart for each specific series and function.

Finish

Stainless Steel Finishes

Satin Stainless Steel	SS
Polished Stainless Steel	PS
Powdercoat	PC*
316 Marine Grade	MG

Brass Finishes

Polished Brass	PB

* Note 1 - Powdercoat finish is not available with engraving options.

2. Product description and its intended use(s)

The 214 Series Door Furniture is 300 x 100 x 2mm thick stainless steel or brass plates with 10mm radius corners. Concealed fixed plates have studs with internal threads located in each corner, visible plates have corresponding countersunk holes and are fixed back-to-back through the door.

Designed for use with Lockwood 3570 Synergy Series and 3770 Selector Series Mortice Locks.

3. Place of Manufacture:

Place of Manufacture

☐ Aotearoa New Zealand   ☒ Overseas, see manufacturer section for details

4. Legal and trading name of the manufacturer(s):

ASSA ABLOY Australia Pty Ltd.

Address for Service

Street name and number	235 Huntingdale Road
Suburb	Oakleigh
Region/state	Victoria
Country	Australia
Post code	3166
Website	https://www.assaabloy.com.au/
Email	https://www.assaabloy.com/au/en/contact-us
Phone	+61 3 8574 3619
Business number	ABN: 90 086 451 907

5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd

Address for Service

Street name and number	6 Armstrong Road
Suburb	Rosedale
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	https://www.assaabloy.com/nz/en
Email	nzsales@assaabloy.com
Phone	+64 (09) 448 9188
Business number	NZBN: 9429036762194

ASSA ABLOY
Experience a safer and more open world

6. Relevant Building Code clauses:

- B2 Durability: Performance clauses B2.3.1(c) (i) and (ii)
- C3 Fire affecting areas beyond the fire source: Functional requirement C3.3
- C4 Movement to place of safety: Functional requirement C4.2
- D1 Access routes: Performance clauses D1.3.1 and D1.3.2 (b)

7. Statement on how the building product is expected to contribute to compliance.

- B2.3.1(c) (i) and (ii): Successfully tested to confirm with Level D8 (500,000) cycles under Australian Standard AS4145.2-2008, locksets and hardware for doors and windows.
- C3.3 and C4.2: Successfully tested up to 4 hours with a fire rated Lockwood mortice lock on fire door assemblies (depending on type of doorset) in accordance with Australian Standard AS1905.1, Fire Resistant Doorsets.
- D1.3.1 and D1.3.2(b): Series includes levers and turns that meet the requirements of AS1428.1-2009, Design for access and mobility. Refer to the specifications for compliant models.

8. Limitations on the use of the building product:

- Suitable for door thickness of 35mm to 45mm standard. For doors 45 to 55mm thick, specify long fixing screws SP2000-208.
- Certain functions require certain handles to be used. The following table outlines which length handles (screw centre distance shown) should be used for a given function.

D Handle Selections				
Handle 17.5mm	P1	P2	P3	P4
Centres	108mm	152mm	203mm	250mm

Function	Description	No Engraving	With Engraving
24	Pull Handle Only	P4	P3
25	Pull Handle and Cylinder	P2	P2
26	Pull Handle and Emergency Turn	P2	P2
27	Pull Handle and Turn Knob	P2	P2
28	Pull Handle and Privacy Indicator Emergency Turn	P2	P2
42	Pull Handle and Disabled Turn	P2	P1
44	Pull Handle Only – Offset from Bottom	P1 P2	x

Note: x indicates this function is not available in this configuration.

9. Design requirements that would support the appropriate use of the building product.

Door furniture with compliance with AS1428.1. Designed for use with Lockwood 3570 Synergy Series and 3770 Selector Series Mortice Locks

10. Installation requirements

- Only use with supplied hardware and ensure the correct door and door hardware is used to ensure fire rating suitability.

11. Maintenance requirements

- Refer to the online general maintenance guide: https://www.lockweb.com.au/au/en/contact-us/product-care-and-specification-service

- Only use with supplied hardware and follow all instructions.
- Clean the external surfaces with a dry cloth only or if required a dilute solution of a mild liquid detergent in warm water, do not use chemicals.
- Door alignment and maintenance is essential to maintain locking alignment and performance.

12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

☐ Yes   ☒ No

If yes, description of the warning or ban under section 26.

N/A

13.   Date

Date of document completion (day/month/year)

2	4	1	1	2	0	2	3