

## 1. Unique identification code of the product-type:

<b>Brand</b>	Lockwood
<b>Model(s)</b>	Entrance Handles 141, 142, 143, 145, 146, 147, 148, 151, 192, 231
<b>Part Number / identifier</b>	See table below
<b>Bar code</b>	N/A
<b>Description/Type</b>	Door furniture – Entrance Handles Various styles and finishes (see table below and website) <a href="https://www.lockweb.com.au/au/en/products/door-handles-levers-and-knobs/push-pull-furniture/entrance-handles">https://www.lockweb.com.au/au/en/products/door-handles-levers-and-knobs/push-pull-furniture/entrance-handles</a>
<b>Production type</b>	Batch or mass-produced products
<b>NZ Building Product class</b>	Class 1

Note: There are too many combinations to legibly notate all the models and options, please refer to the chart below for the details.

### Ordering Procedure

Sample part number 141X300SSS is made up of several sections.  
Choose your product by selecting an option from each section.

Design	Centre to Centre	Finish
141	X 300	SSS

Design	Centre to Centre	Finish
141 Style 141	300mm Centres 300 141, 142, 143, 151, 231	Satin Stainless Steel SSS
142 Style 142		
143 Style 143	450mm Centres 450 141, 142, 143, 146, 147, 148, 192	
145 Style 145		
146 Style 146	600mm Centres 600 141, 142, 143, 146, 148, 192	
147 Style 147		
148 Style 148	225mm Centres (145 Style Only) 225	
151 Style 151C		
192 Style 192	375mm Centres (145 Style Only) 375	
231 Style 231C	525mm Centres (145 Style Only) 525	

Design	Centre to Centre	Finish
141 Style 141	600mm Centres 600 141, 143,	Matt Black MBK
143 Style 143		Powdercoated PC

## 2. Product description and its intended use(s)

Lockwood Entrance Handles are constructed using the finest materials to incorporate the maximum standards in style, durability, finish and design. Combining fit for purpose with the epitome of style, the Lockwood Entrance Handles range represents a comprehensive collection of high quality back to back handles. Nine designs, ranging from classic to contemporary, have been selected to complement the evolving style requirements of both residential and commercial markets. Each Lockwood Entrance Handle comes supplied with spigots to suit 10 – 12mm thick glass doors as well as aluminium and timber doors up to 50mm thick. Lockwood Entrance Handles are suitable for use on timber or aluminium frame as well as glass doors; making them the ideal choice for commercial, industrial and residential applications. Fixing bolts are available for timber, aluminium or glass doors. Any full set can be converted into a half set using a concealed fix or disk fix kit.

Generic Model: Entrance Handles

Type: Door furniture

### 3. Place of Manufacture:

Place of Manufacture

Aotearoa New Zealand       Overseas, see manufacturer section for details

### 4. Legal and trading name of the manufacturer(s):

ASSA ABLOY Australia Pty Ltd.

Address for Service

Street name and number	235 Huntingdale Road
Suburb	Oakleigh
Region/state	Victoria
Country	Australia
Post code	3166
Website	<a href="https://www.assaabloy.com.au/">https://www.assaabloy.com.au/</a>
Email	<a href="https://www.assaabloy.com/au/en/contact-us">https://www.assaabloy.com/au/en/contact-us</a>
Phone	+61 3 8574 3619
Business number	ABN: 90 086 451 907

### 5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd

Address for Service

Street name and number	6 Armstrong Road
Suburb	Rosedale
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	<a href="https://www.assaabloy.com/nz/en">https://www.assaabloy.com/nz/en</a>
Email	nzsales@assaabloy.com
Phone	+64 (09) 448 9188
Business number	NZBN: 9429036762194

Generic Model: Entrance Handles

Type: Door furniture

## 6. Relevant Building Code clauses:

- B2 Durability: Performance clauses B2.3.1(c) (i) and (ii)
- C3 Fire affecting areas beyond the fire source: Functional requirement C3.3
- C4 Movement to place of safety: Functional requirement C4.2
- D1 Access routes: Performance clauses D1.3.1 and D1.3.2 (b)

## 7. Statement on how the building product is expected to contribute to compliance.

- B2.3.1(c) (i) and (ii): Successfully tested to confirm with Level D8 (500,000) cycles under Australian Standard AS4145.2-2008, locksets and hardware for doors and windows.
- C3.3 and C4.2: Successfully tested up to 4 hours with a fire rated Lockwood mortice lock on fire door assemblies (depending on type of doorset) in accordance with Australian Standard AS1905.1, Fire Resistant Doorsets.
- D1.3.1 and D1.3.2(b): Series includes levers and turns that meet the requirements of AS1428.1-2009, Design for access and mobility. Refer to the specifications for compliant models.

## 8. Limitations on the use of the building product:

- Suitable for door thickness of 35mm to 45mm standard. For doors 45 to 55mm thick, specify long fixing screws SP2000-208.

## 9. Design requirements that would support the appropriate use of the building product.

Door furniture with compliance with AS1428.1 (excluding Lockwood Entrance handle style 192).  
Designed for use with Lockwood 3570 Synergy Series and 3770 Selector Series Mortice Locks


## 10. Installation requirements

- Only use with supplied hardware and ensure the correct door and door hardware is used to ensure fire rating suitability.
- Lockwood Entrance Handles can be supplied with a number of supplementary accessories that allow for the flexibility to convert back to back fixing full sets to disk fix or concealed fix half sets. All available options listed suit 10-12mm thick glass doors and 50mm thick timber and aluminum doors unless otherwise specified.

### Standard Full Set

#### Back to Back Fix Accessories


Part Number	Timber Fixing	Glass Fixing
SP-1EHM8	2 x 80mm M8 Screws	2 x 40mm M8 Screws
SP-2EHM6S	2 x 62mm M6 Spigot Screws	2 x 32mm M6 Spigot Screws
SP-3EHM8S	2 x 70mm M8 Spigot Screws	2 x 30 mm M8 Screws



### Half Set Options


#### Concealed Fix Accessories

Part Number	Timber Fixing	Glass Fixing
SP-4EHCF	2 x Ø15mm Spigots 2 x 45mm M6.3 (14G) Screws	N/A
SP-5EHCF	2 x Ø10mm Spigots 2 x 38mm M4.5 (8G) Screws	N/A



#### Disk Fix Accessories

Part Number	Timber Fixing	Glass Fixing
SP-6EHDFM8	2 x 70mm M8 Disk Fit Screw	2 x 30mm M8 Disk Fit Screw
SP-7EHDFM6	2 x 70mm M6 Disk Fit Screw	2 x 30mm M6 Disk Fit Screw



Handle Style	Full Set Back to back	Half Set Concealed Fix	Half Set Disk Fix
141	SP-1EHM8*	SP-4EHCF	SP-6EHDFM8
142	SP-1EHM8*	SP-4EHCF	SP-6EHDFM8
143	SP-2EHM6S*	SP-5EHCF	SP-7EHDFM6
145	SP-3EHM8S*	SP-4EHCF	SP-7EHDFM6
146	SP-1EHM8*	SP-4EHCF	SP-6EHDFM8
147	SP-3EHM8S	SP-4EHCF	SP-7EHDFM6
148	SP-1EHM8*	SP-4EHCF	SP-6EHDFM8*
151	SP-1EHM8*	SP-4EHCF	SP-6EHDFM8
192	SP-1EHM8*	SP-4EHCF	SP-6EHDFM8
231	SP-1EHM8*	SP-4EHCF	SP-6EHDFM8

Note: The screw packs marked with a \* are the standard bolts that are supplied with the Entrance Handles. Each full set can be converted into 1 x Concealed Fix Half Set and 1 x Disk Fit Half Set only.

## 11. Maintenance requirements

- Refer to the online general maintenance guide: <https://www.lockweb.com.au/au/en/contact-us/product-care-and-specification-service>
- Only use with supplied hardware and follow all instructions.
- Clean the external surfaces with a dry cloth only or if required a dilute solution of a mild liquid detergent in warm water, do not use chemicals.
- Door alignment and maintenance is essential to maintain locking alignment and performance.

## 12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

Yes  No

If yes, description of the warning or ban under section 26.

N/A

## 13. Date

Date of document completion (day/month/year)

2 4 1 1 2 0 2 3