

Generic: Pinnacle Sliding Door Lock

Type: Mortise Sliding Door Lock

1. Unique identification code of the product-type:

Brand	ASSA ABLOY
Model(s)	Pinnacle Sliding Door Lock 30mm, 35mm and 40mm
Part Number / identifier	Pinnacle Sliding Door
Bar code	-
Description/Type	Pinnacle Sliding Door Mortise Lock with and without door furniture
Production type	Batch or mass-produced products
NZ Building Product class	Class 1

2. Product description and its intended use(s)

The Pinnacle Sliding Door Lock is to be used in sliding door applications. The lock features the unique security of a single hookbolt with an anti-lift feature between the lock and the strike.

Key Features:

- Adjustable strike with additional 3mm packer (sold separately)
- 30mm, 35mm, 40mm backset Yale Pinnacle mortice lock
- Deadbolt locking
- Anti-lift design
- Anti-slam mechanism protects accidental damage to hook bolt when door is closed
- Stainless steel forend plate
- Robust design
- Built to withstand a 4kN force entry load and 100,000 locking cycles
- Identical standard routing details to Optimum Mortice Locks
- Can be keyed alike to other ASSA ABLOY CYL4™ 5-Pin locks for one key convenience
- Supplied in trade pack
- New Zealand made

Applications:

- Suitable for sliding door applications, which can be morticed to fit lock body.

3. Place of Manufacture:

Place of Manufacture

- Aotearoa New Zealand Overseas, see manufacturer section for details

Generic: Pinnacle Sliding Door Lock

Type: Mortise Sliding Door Lock

4. Legal and trading name of the manufacturer(s):

ASSA ABLOY New Zealand Ltd.

Address for Service

Street name and number	6 Armstrong Road
Suburb	Albany
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	https://www.assaabloy.com/nz/en
Email	nzsales@assaabloy.com
Phone	+64 (0) 9 448 9188
Business number	NZBN: 9429036762194

5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd

Address for Service

Street name and number	
Suburb	
Region/state	
Country	
Post code	
Website	
Email	
Phone	
Business number	

6. Relevant Building Code clauses:

Standard	Clause(s)
Building Regulations 1992	B2.3.1 – Durability; Performance
Building Regulations 1992	D1 – Access routes D1.3.1 (b), D1.3.4 (f)

Generic: Pinnacle Sliding Door Lock

Type: Mortise Sliding Door Lock

7. Statement on how the building product is expected to contribute to compliance.

B2.3.1 (c) The Pinnacle SD Lock is designed to meet the normal use over a 5 year period and any failure of the product is easily detected and is easy to replace.

D1.3.1 (b) (c) The Pinnacle SD Lock allows for sliding doors which can be used as entrance or internal doors allowing people to enter and move into spaces within buildings.

D1.3.4 (f) The Pinnacle SD Lock allows for sliding doors to be easily used for accessible routes.

8. Limitations on the use of the building product:

- The Pinnacle SD lock is not fire rated and is designed to be used for residential use.
- Refer to the installation instructions for correct fitment
- Complies with AS4145.2-2008 Australian Standard Locksets and hardware for doors and windows

9. Design requirements that would support the appropriate use of the building product.

Must be installed as per instructions

10. Installation requirements

- Refer to the Pinnacle routing details available
- https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/RES_FLY_089NZ.pdf
- Range of strikes available for many applications

11. Maintenance requirements

- Clean the external surfaces with a dry cloth only, do not use chemicals.
- Door alignment and maintenance is essential to maintain locking alignment and performance.

12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

Yes No

If yes, description of the warning or ban under section 26

N/A

13. Date

Date of document completion (day/month/year)

2	1	1	1	2	0	2	3
---	---	---	---	---	---	---	---