

1. Unique identification code of the product-type:

Brand	ASSA ABLOY
Model(s)	Mawson Sliding Door Lock
Part Number / identifier	Mawson Sliding Door Lock
Bar code	-
Description/Type	Mawson Surface Mounted Sliding Door Lock
Production type	Batch or mass-produced products
NZ Building Product class	Class 1

2. Product description and its intended use(s)

The Mawson Sliding Door Lock. Suitable for use with aluminium, uPVC and timber sliding doors.

Features

- Anti-lift pins for added security
- Self-retracting beak avoids damage and accidental locking
- Ideal for replacement applications of standard 82mm mounting screw hole centres
- Suitable for left or right handed sliding doors
- Can be keyed alike for One Key Security
- Secure 5-pin cylinder for durability and security
- Supplied in trade pack

Applications:

- For use with aluminium, uPVC and timber sliding doors, either as a new installation or to replace an existing lock.

3. Place of Manufacture:

Place of Manufacture

- Aotearoa New Zealand Overseas, see manufacturer section for details

4. Legal and trading name of the manufacturer(s):

ASSA ABLOY Australia Pty Ltd.

Address for Service

Street name and number	235 Huntingdale Road
Suburb	Oakleigh
Region/state	Victoria
Country	Australia
Post code	3166
Website	https://www.assaabloy.com.au/
Email	https://www.assaabloy.com/au/en/contact-us
Phone	+61 3 8574 3619
Business number	ABN: 90 086 451 907

5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd

Address for Service

Street name and number	6 Armstrong Road
Suburb	Albany
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	https://www.assaabloy.com/nz/en
Email	nzsales@assaabloy.com
Phone	+64 (0) 9 448 9188
Business number	NZBN: 9429036762194

6. Relevant Building Code clauses:

Standard	Clause(s)
Building Regulations 1992	B2.3.1 – Durability; Performance
Building Regulations 1992	D1 – Access routes D1.3.1(b), D1.3.4(f)

7. Statement on how the building product is expected to contribute to compliance.

B2.3.1 (c) The Mawson sliding door lock is designed to meet the normal use over a 5 year period and any failure of the product is easily detected and is easy to replace.
D1.3.1 (b) The Mawson sliding door lock allows for sliding doors that can be used as entrance doors allowing people to enter buildings.
D1.3.4 (f) The Mawson sliding door lock allows for sliding doors to be easily used for accessible routes

8. Limitations on the use of the building product:

- The Mawson mortise lock is not fire rated and is designed to be used for residential use.
- Refer to the installation instructions for correct fitment
- Complies with AS4145.2-2008 Australian Standard Locksets and hardware for doors and windows

9. Design requirements that would support the appropriate use of the building product.

Must be installed as per instructions

10. Installation requirements

- Refer to the installation instructions available
- [Q25131_Mawson_Fitting_Instructions.pdf \(assaabloyopeningsolutions.nz\)](#)
- [Whitco Sliding Door Hardware Catalogue.pdf \(assaabloyopeningsolutions.nz\)](#)
- Range is strikes available for many applications

11. Maintenance requirements

- Clean the external surfaces with a dry cloth only, do not use chemicals.
- Door alignment and maintenance is essential to maintain locking alignment and performance.

12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

Yes No

If yes, description of the warning or ban under section 26

N/A

13. Date

Date of document completion (day/month/year)

2	1	1	1	2	0	2	3
---	---	---	---	---	---	---	---