

1. Unique identification code of the product-type:

Brand	Interlock
Model(s)	4 Bar Stays
Part Number / identifier	P1001 P1002 P1002NF P1003 P1003NF P1004 P1004NF
Bar code	N/A
Description/Type	Window Stay
Production type	Batch or mass-produced products
NZ Building Product class	Class 1

2. Product description and its intended use(s)

Support and frictional control of projecting top hung sashes

Key Features:

- Non-handed
- Manufactured with the unique inch pull in inch feature.
- No sliding channels.
- Factory set friction levels mean no on-site adjustment is required.
- Fixed directly through the bearing eyelet as well as through the formed screw or rivet holes.
- Incorporates patented frictional bearing.
- Includes specific function model type of Friction, reduced friction or non-friction for use with window control mechanisms.
- Supplied in trade pack as a pair

Applications:

- Timber, Aluminium window fixing surfaces.
- Awning window
- Available in 3 sizes, designated by the frame plate length, catering for sashes weighing up to 30kg. The selection of which is determined by the sash weight and height

3. Place of Manufacture:

Place of Manufacture

- Aotearoa New Zealand Overseas, see manufacturer section for details

Generic Model: 4 Bar Stay

Type: Window Stay

4. Legal and trading name of the manufacturer(s):

METCO ENGINEERING

Address for Service

Street name and number	1E Quadrant Drive
Suburb	Lower Hutt
Region/state	Wellington
Country	New Zealand
Post code	5010
Website	https://metco.co.nz/
Email	https://metco.co.nz/contact/
Phone	+64 (0) 4 567 3222
Business number	

5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd

Address for Service

Street name and number	6 Armstrong Road
Suburb	Albany
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	https://www.assaabloy.com/nz/en
Email	nzsales@assaabloy.com
Phone	+64 (09) 448 9188
Business number	NZBN: 9429036762194

6. Relevant Building Code clauses:

Standard	Clause(s)
Building Regulations 1992	B2 Durability – Performance Clause B2.3.1
Building Regulations 1992	H1 Energy efficiency – Performance Clauses H1.3.1 (b), H1.3.3 (c)

Generic Model: 4 Bar Stay

Type: Window Stay

7. Statement on how the building product is expected to contribute to compliance.

B2.3.1 The window stay has been tested to a durability of 36,000 cycle to service the life of the building.

H1.3.1 (b) This limits any uncontrollable airflow and contributes to the airtightness of the building envelope.

H1.3.3 (c) The window stay will allow the window sash to form a weathertight seal upon closure.

8. Limitations on the use of the building product:

Selection of the product type determined by the sash weight and height.
To be used to seal and ventilate windows only.

9. Design requirements that would support the appropriate use of the building product.

Refer to product-specific design instructions online:

<https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/4B%20Series%20Friction%20Stay%20Technical%20Flyer.pdf>

10. Installation requirements

Customer to refer to product-specific design instructions online to suit the window installation requirement:

<https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/4B%20Series%20Friction%20Stay%20Technical%20Flyer.pdf>

11. Maintenance requirements

N/A

12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

Yes

No

If yes, description of the warning or ban under section 26

13. Date

Date of document completion (day/month/year)

1	4	1	1	2	0	2	3
---	---	---	---	---	---	---	---