

1. Unique identification code of the product-type:

Brand	Yale, Interlock
Model(s)	Nexus HCA STAY
Part Number / identifier	P240*, P340*, P450H, P710H
Bar code	N/A
Description/Type	Window Stay
Production type	Batch or mass-produced products
NZ Building Product class	Class 1

2. Product description and its intended use(s)

Key Features:

- Patent pending for new innovative integrated friction joint
- Geometry optimized for window range
- Manufactured with the unique 'pull-in' feature
- Identification mark for High Friction versions
- No sliding channels
- Black powdercoat finish
- Supplier in trade pack as a pair

Applications:

- Projected top hung windows
- Direct replacement for the current A-Stay range
- Available in four sizes to cater for sashes weighing up to 60kg. Includes specific function models:
 - 'A' Standard friction
 - 'H' High friction
 - 'N' Non-friction

3. Place of Manufacture:

Place of Manufacture

- Aotearoa New Zealand
 Overseas, see manufacturer section for details

4. Legal and trading name of the manufacturer(s):

ASSA ABLOY(ZHONGSHAN) SECURITY

Address for Service

Street name and number	33-35, Chrysanthemum Road East
Suburb	Xiaolan, Zhongshan
Region/state	Guangdong
Country	China
Post code	528415
Website	https://www.assaabloy.cn/en
Email	https://www.assaabloy.cn/en/contact-us
Phone	+86 (0)760 2210 2326 Ext 3006
Business number	

5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd

Address for Service

Street name and number	6 Armstrong Road
Suburb	Albany
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	https://www.assaabloy.com/nz/en
Email	nzsales@assaabloy.com
Phone	+64 (09) 448 9188
Business number	NZBN: 9429036762194

6. Relevant Building Code clauses:

Standard	Clause(s)
Building Regulations 1992	B2 Durability – Performance Clause B2.3.1
Building Regulations 1992	H1 Energy efficiency – Performance Clause H1.3.1, H1.3.3

7. Statement on how the building product is expected to contribute to compliance.

The window stay has been tested to a durability of 36,000 cycle to service the life of the building.

The window stay will allow the window sash to form a weathertight seal upon closure. This limits any uncontrollable airflow and contributes to the airtightness of the building envelope

8. Limitations on the use of the building product:

Selection of the product type determined by the sash weight and height.
To be used to seal and ventilate windows only.

9. Design requirements that would support the appropriate use of the building product.

Refer to product-specific design instructions online:

https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/NEXUSBRO_YA_EN_SP1.pdf

https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/NEXUSBRO_YA_EN_TS1.pdf

https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/YANEXUSCHARTA2_YA_EN_TS1.pdf

10. Installation requirements

Customer to refer to product-specific design instructions online to suit the window installation requirement:

https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/NEXUSBRO_YA_EN_SP1.pdf

https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/NEXUSBRO_YA_EN_TS1.pdf

https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/YANEXUSCHARTA2_YA_EN_TS1.pdf

11. Maintenance requirements

N/A

12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

Yes

No

If yes, description of the warning or ban under section 26

13. Date

Date of document completion (day/month/year)

0	6	1	2	2	0	2	3
---	---	---	---	---	---	---	---