

1. Unique identification code of the product-type:

Brand	Yale
Model(s)	CHH STAY
Part Number / identifier	P362B, P363B, P364B, P568B
Bar code	N/A
Description/Type	Window Stay
Production type	Batch or mass-produced products
NZ Building Product class	Class 1

2. Product description and its intended use(s)

4-bar friction stays manufactured from extruded Aluminium. Used for residential applications.

Key Features:

- For retrofit applications
- Manufactured with the unique inch pull in inch feature.
- No sliding channels.
- Factory set friction levels mean no on-site adjustment is required.
- Black powdercoat finish
- Supplied in trade pack as a pair

Applications:

- Timber, Aluminium window fixing surfaces
- Projected top hung windows
- Available in four sizes to cater for sashes weighing up to 16kg and sash height up to 1200mm.

3. Place of Manufacture:

Place of Manufacture

☐

Aotearoa New Zealand

☒

Overseas, see manufacturer section for details

4. Legal and trading name of the manufacturer(s):

GUANGDONG AURICAN ARCHITECTURAL HARDWARE CO. LTD.

Address for Service

Street name and number	No.06B3 Block, Shengping 2nd Industrial Area
Suburb	Shantou
Region/state	Guangdong
Country	China
Post code	528415
Website	http://www.aurican.com/en/index.php
Email	http://www.aurican.com/en/contact.php
Phone	+86 (754) 88206813
Business number	

5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd

Address for Service

Street name and number	6 Armstrong Road
Suburb	Albany
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	https://www.assaabloy.com/nz/en
Email	nzsales@assaabloy.com
Phone	+64 (09) 448 9188
Business number	NZBN: 9429036762194

6. Relevant Building Code clauses:

Standard	Clause(s)
Building Regulations 1992	B2 Durability – Performance Clause B2.3.1
Building Regulations 1992	H1 Energy efficiency – Performance Clause H1.3.1, H1.3.3

7. Statement on how the building product is expected to contribute to compliance.

The window stay has been tested to a durability of 36,000 cycle to service the life of the building.

The window stay will allow the window sash to form a weathertight seal upon closure. This limits any uncontrollable airflow and contributes to the airtightness of the building envelope

8. Limitations on the use of the building product:

Selection of the product type determined by the sash weight and height.

To be used to seal and ventilate windows only.

9. Design requirements that would support the appropriate use of the building product.

Refer to product-specific design instructions online:

https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/Q13020_Y_Friction_Stay_Generic_Instructions_Label.pdf

10. Installation requirements

Customer to refer to product-specific design instructions online to suit the window installation requirement:

https://eshop.assaabloyopeningsolutions.nz/media/B2BUserGuide/Q13020_Y_Friction_Stay_Generic_Instructions_Label.pdf

11. Maintenance requirements

N/A

12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

☐ Yes

☒ No

If yes, description of the warning or ban under section 26

☒

13. Date

Date of document completion (day/month/year)

0	6	1	2	2	0	2	3
---	---	---	---	---	---	---	---