1. Unique identification code of the product-type:

Brand	Lockwood			
Model(s)	001 Double Cylinder Deadlatch (Knob version)			
Variant	001 - 1K1 with Open In Strike - Single Pack			
Finish	**Model Trade pack**	**Bar code # Trade Pack**	**Model Display pack**	**Bar code # Display Pack**
Satin Chrome Pearl	L001-1K1SP		L001-1K1SPDP	
Chrome Plate			L001-1K1CPDP	
Brown			L001-1K1BRNDP	
Everbrass			L001-1K1EVBDP	
Matt Black	001-1K1MBK		001-1K1MBKDP	
Description/Type	Door lock (Double Cylinder Deadlatch) Suitable for INWARD opening timber framed doors.			
Production type	Batch or mass-produced products			
NZ Building Product class	Class 1			

Brand	Lockwood			
Model(s)	001 Double Cylinder Deadlatch (Knob version)			
Variant	001 - 1K2 with Open In Strike - Twin Pack			
Finish	**Model Trade pack**	**Bar code # Trade Pack**	**Model Display pack**	**Bar code # Display Pack**
Satin Chrome Pearl			L001-1K2SPDP	
Bright Chrome			L001-1K2CPDP	
Everbrass			L001-1K2EVBDP	
Description/Type	Door lock (Double Cylinder Deadlatch) Suitable for INWARD opening timber framed doors. Keyed alike for extra convenience. Pack contains two locksets			
Production type	Batch or mass-produced products			
NZ Building Product class	Class 1			

Brand	Lockwood			
Model(s)	001 Double Cylinder Deadlatch (Knob version)			
Variant	001 - 3K1 with Metal Frame Strike - Single Pack			
Finish	Model Trade pack	Bar code # Trade Pack	Model Display pack	Bar code # Display Pack
Satin Chrome Pearl	L001-3K1SP		---	
Matt Black	001-3K1MBK			
Description/Type	Door lock (Double Cylinder Deadlatch) Suitable for INWARD opening metal framed doors.			
Production type	Batch or mass-produced products			
NZ Building Product class	Class 1			

Brand	Lockwood			
Model(s)	001 Double Cylinder Deadlatch (Knob version)			
Variant	001 - 4K1 with Open Out Strike - Single Pack			
Finish	Model Trade pack	Bar code # Trade Pack	Model Display pack	Bar code # Display Pack
Satin Chrome Pearl	L001-4K1SP		---	
Description/Type	Door lock (Double Cylinder Deadlatch) Suitable for OUTWARD opening timber framed doors.			
Production type	Batch or mass-produced products			
NZ Building Product class	Class 1			

Brand	Lockwood			
Model(s)	001 Double Cylinder Deadlatch (lever version)			
Variant	001 - 1L1 with Open In Strike - Single Pack			
Finish	Model Trade pack	Bar code # Trade Pack	Model Display pack	Bar code # Display Pack
Satin Chrome Pearl	L001-1L1SP		L001-1L1SPDP	
Everbrass	---		L001-1L1EVBDP	
Description/Type	Door lock (Double Cylinder Deadlatch) Suitable for INWARD opening timber framed doors.			
Production type	Batch or mass-produced products			
NZ Building Product class	Class 1			

Brand	Lockwood			
Model(s)	001 Double Cylinder Deadlatch (lever version)			
Variant	001 - 4L1 with Metal Frame Strike - Single Pack			
Finish	**Model Trade pack**	**Bar code # Trade Pack**	**Model Display pack**	**Bar code # Display Pack**
Satin Chrome Pearl	L001-4L1SP		---	
Description/Type	Door lock (Double Cylinder Deadlatch) Suitable for OUTWARD opening timber framed doors.			
Production type	Batch or mass-produced products			
NZ Building Product class	Class 1			

2. Product description and its intended use(s)

The Australian-designed Lockwood 001® Deadlatch offers market-leading performance and reliability for your home and is available in both Knob and Lever versions. The 001® Deadlatch features a cut-resistant stainless-steel bolt, 11 concealed anchorage points and a door frame strengthener that combine to offer high security protection. Additional features include a bolt hold back function that allows you to use your door in passage mode.

Features and Specifications
- Bolt hold-back function activated by external key or internal knob
- Can be key locked in hold-back position by key from inside
- Can be keyed alike to other Lockwood door locks
- Available in trade and display pack versions

Keying
- Supplied individually keyed with two keys per lock
- 78,000 key combinations
- Key blank KB2015

	001
Backset	60mm
Case	Zinc
Door thickness	30 – 45mm
Latch	Steel
Fire rated	No
Conforms to Australian Standard (AS4145.2-2008)	SL7 (Second to highest) D8 (Highest) C6 (168 hours)

* https://www.assaabloy.com/nz/en/solutions/products/hinged-door-locks/rimlocks

3. Place of Manufacture:

Place of Manufacture

☐ Aotearoa New Zealand ☒ Overseas, see manufacturer section for details

4. Legal and trading name of the manufacturer(s):

ASSA ABLOY Australia Pty Ltd.
Address for Service

Street name and number	235 Huntingdale Road
Suburb	Oakleigh
Region/state	Victoria
Country	Australia
Post code	3166
Website	https://www.assaabloy.com.au/
Email	https://www.assaabloy.com/au/en/contact-us
Phone	+61 3 8574 3619
Business number	ABN: 90 086 451 907

ASSA ABLOY(ZHONGSHAN) SECURITY
Address for Service

Street name and number	33-35, Chrysanthemum Road East
Suburb	Xiaolan, Zhongshan
Region/state	Guangdong
Country	China
Post code	528415
Website	https://www.assaabloy.cn/en
Email	https://www.assaabloy.cn/en/contact-us
Phone	+86 (0)760 2210 2326 Ext 3006
Business number	

5. Legal and trading name of the importer (if applicable):

ASSA ABLOY New Zealand Ltd
Address for Service

Street name and number	6 Armstrong Road
Suburb	Rosedale
Region/state	Auckland
Country	New Zealand
Post code	0632
Website	https://www.assaabloy.com/nz/en
Email	nzsales@assaabloy.com
Phone	+64 (09) 448 9188
Business number	NZBN: 9429036762194

6. Relevant Building Code clauses:

Standard	Clause(s)
Building Regulations 1992	B2.3.1 – Durability; Performance
Building Regulations 1992	D1 – Access routes D1.3.1 (b), D1.3.2 (b)
Building Regulations 1992	C3.3 – Fire affecting areas beyond the fire source
Building Regulations 1992	C4.2 – Movement to a place of safety

7. Statement on how the building product is expected to contribute to compliance.

- B2.3.1(c) (i) and (ii): Successfully tested to confirm with Level D8 (500,000) cycles under Australian Standard AS4145.2-2008, locksets and hardware for doors and windows.
- C3.3 and C4.2: Successfully tested up to 2 hours with a fire rated Lockwood mortice lock on fire door assemblies (depending on type of doorset) in accordance with Australian Standard AS1905.1, Fire Resistant Doorsets.
- D1.3.1 and D1.3.2 (b): Series includes levers and turns that meet the requirements of AS1428.1-2009, Design for access and mobility. Refer to the specifications for compliant models.

8. Limitations on the use of the building product:

- Fixing screws to suit door thickness between 30 and 45mm

9. Design requirements that would support the appropriate use of the building product.

- Securing doors (allowing locking of doors).
- Kinetic Defence® Bump and pick resistant.
- SafetyRelease™ - Minimises the risk of being locked in.
- LockAlert® Interior Indicator shows lock status at a glance.
- Safety Mode Securely locked from outside and free from inside.
- Secure Mode Securely locked from both inside and outside. For when nobody is home.
- Passage Mode Free to enter from outside and free to exit from inside.
- Deadlatch Bolt Stainless steel 18mm projection.
- 2 Keys Included Can be keyed alike to other Lockwood door locks.
- Retrofitable Replace your existing 001 Deadlatch™.

10. Installation requirements

- Only use with supplied hardware and ensure the correct door and door hardware is used to ensure fire rating suitability.

11. Maintenance requirements

- Refer to the online general maintenance guide: https://www.lockweb.com.au/au/en/contact-us/product-care-and-specification-service
- Only use with supplied hardware and follow all instructions.
- Clean the external surfaces with a dry cloth only or if required a dilute solution of a mild liquid detergent in warm water, do not use chemicals.
- Door alignment and maintenance is essential to maintain locking alignment and performance.

12. Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

☐ Yes ☒ No

If yes, description of the warning or ban under section 26.

N/A

13. Date

Date of document completion (day/month/year)

0	7	1	0	2	0	2	6