

VELARO SOFT STOP

For top hung glass sliding doors. Max 80kg each leaf.

APPLICATION

- Stylish design with a modern and minimalistic finish, all parts concealed within the track
- The soft stop decelerates sliding glass panels and pulls them to their final position
- Single and double dampers available
- Designed for glass doors of up to 80kg and suits 8, 10 and 12mm door thicknesses
- For interior residential or commercial applications
- Ideal for soffit, soffit panel and face fixed installations
- Polymer rollers and brush strip within the track ensure a quiet and smooth operation
- High quality stainless steel hangers and brackets
- Compact glass clamp requires no holes in glass panels

DOOR SPECIFICATION

Track System	Velaro
For Individual Door Leaves:	
Max Door Weight	80kg
Max Door Width	1200mm
Glass Thickness	8, 10, 12mm
Max Door Height	2500mm

Single damper	
Min Panel Width	806mm

Double damper	
Min panel width	1140mm

Glass Weight
Value is approximate based on
8mm glass panel = 20kg/m ²
10mm glass panel = 25kg/m ²
12mm glass panel = 30kg/m ²

STANDARD SINGLE DAMPER SETS AND PACK

Sets comprise of 2 clamps with gaskets, LH and RH wheel carriage, single damper assembly
Activation bracket, end stop block, floor guide

8mm	HVS80/8
10mm	HVS8/10
12mm	HVS8/12

STANDARD DOUBLE DAMPER SETS AND PACK

Sets comprise of 2 clamps with gaskets, LH and RH wheel carriage, double damper assembly
Activation bracket, end stop block, floor guide

8mm	HVD80/8
10mm	HVD8/10
12mm	HVD8/12

HARDWARE SPECIFICATION

Tracks	HV80FF	Anodised aluminium face fix track (2000, 2500, 3000, 3500, 4000 & 5000mm lengths)
	HV80SF	Anodised aluminium soffit fix track (2000, 2500, 3000, 3500, 4000 & 5000mm lengths)
	HV80FP	Anodised aluminium fixed panel track (2000, 2500, 3000, 3500, 4000 & 5000mm lengths)
		<i>Lengths include brush strips and end caps</i>
Guide	H8-12/SN	Brushed stainless steel adjustable floor guide to suit 8, 10 or 12mm glass

Accessories

Handles Refer to your **Lockwood Catalogue** for a full range of handles



