

SOLTAIRE LOW HEADROOM 120

For timber top hung sliding doors. Max 120kg.

APPLICATION

- Designed to create a modern minimalist finish with all parts concealed
- Can reduce the clearance between the track and the top of the door to 2mm
- Vertically adjustable sliding door kit for low or restricted headroom applications
- Used to maximise door height
- Engineered for easy installation and adjustment
- Designed to accommodate single or multiple panels on one or more tracks

DOOR SPECIFICATION

Track System **Low Headroom 120**

For Individual Door Leaves:

Max Door Weight	120kg
Door Thickness	35-48mm*
Max Door Height	2700mm

* For doors thicker than 48mm, please contact our technical sales team for further information.

STANDARD PACK

Pack comprises of 2x Low Headroom units, 2x end caps, 2x track stops, all screws and fitting instructions.

Pack No.	Application
HLH120	1 door pack

HARDWARE SPECIFICATION

Track	H120	Aluminium (2000, 3000, 4000 & 6000mm lengths)
	H120A	Anodised Aluminium (2000, 3000, 4000 & 6000mm lengths) Soffit fix spacing 600mm centres (maximum)
Brackets	H1/SS	Face fixed stainless steel
	H5/SS/120	Double face fixed stainless steel Starting 20mm from end of track fix at 600mm centres (maximum)
Track Stop	HH4/SS	Anodised aluminium with rubber buffer
Guides	H102N	Nylon saw cut guide
	H102SS/94	Timber doors - wall mounted and multiple run guide
	H105SS/94	Timber doors - face mounted guide
	H106SS/94	Timber doors - concealed fixing with SS bearing
Channels	H94X	Aluminium (2000, 3000, 4000 & 6000mm lengths)
	H94	Brass (1500 & 3000mm lengths)
	H94P	Polypropylene (2000, 3000, 4000 & 6000mm lengths)
	H94PSC	Aluminium supporting channel and polypropylene (2000, 3000, 4000 & 6000mm lengths)
Accessories		
Interlocking Seal	H59BZ/4800	Bronze anodised (4800mm to suit typical 2400mm door height)
	H59CA/4800	Clear anodised aluminium (4800mm to suit typical 2400mm door height) Drilled and countersunk. Includes brush seal.



