

SOLTAIRE LOW HEADROOM 180

For timber top hung sliding doors. Max 180kg.

APPLICATION

- Designed to create a modern minimalist finish with all parts concealed
- Can reduce the clearance between the track and the top of the door to 2mm
- Vertically adjustable sliding door kit for low or restricted headroom applications
- Used to maximise door height
- Engineered for easy installation and adjustment
- Designed to accommodate single or multiple panels on one or more tracks

DOOR SPECIFICATION

Track System **Low Headroom 180**

For Individual Door Leaves:

Max Door Weight	180kg
Max Door Width	3300mm
Door Thickness	35-48mm*
Max Door Height	2700mm

* For doors thicker than 48mm, please contact our technical sales team for further information.

STANDARD PACK

Pack comprises of 2x Low Headroom units, 2x end caps, 2x track stops, all screws and fitting instructions.

Pack No.	Application
HLH180	1 door pack

HARDWARE SPECIFICATION

Track	H180A	Anodised Aluminium (2000, 3000, 4000 & 6000mm lengths) Soffit fix spacing 900mm centres (maximum)
Brackets	H1/SS H5H/SS	Face fixed stainless steel Double face fixed stainless steel (heavy) Starting 20mm from each end of track fix at 900mm centres (max.)
Track Stop	HH5/SS	Anodised aluminium with rubber buffer
Guides	H102SS/94 H105SS/94 H106HSS/94	Timber doors - wall mounted and multiple run guide Timber doors - face mounted guide Timber doors - concealed fixing with SS bearing
Channels	H94X H94 H94P H94PSC	Aluminium (2000, 3000, 4000 & 6000mm lengths) Brass (1500 & 3000mm lengths) Polypropylene (2000, 3000, 4000 & 6000mm lengths) Aluminium supporting channel and polypropylene (2000, 3000, 4000 & 6000mm lengths)
Accessories		
Interlocking Seal	H59BZ/4800 H59CA/4800	Bronze anodised (4800mm to suit typical 2400mm door height) Clear anodised aluminium (4800mm to suit typical 2400mm door height) Drilled and countersunk. Includes brush seal.



