

SOLTAIRE LOW HEADROOM 250

For timber top hung sliding doors. Max 250kg.

APPLICATION

- Designed to create a modern minimalist finish with all parts concealed
- Can reduce the clearance between the track and the top of the door to 2mm
- Vertically adjustable sliding door kit for low or restricted headroom applications
- Used to maximise door height
- Engineered for easy installation and adjustment
- Designed to accommodate single or multiple panels on one or more tracks

DOOR SPECIFICATION

Track System **Low Headroom 250**

For Individual Door Leaves:

Max Door Weight	250kg
Door Thickness	35-48mm*
Max Door Height	3300mm

* For doors thicker than 48mm, please contact our technical sales team for further information.


STANDARD PACK

Pack comprises of 2x Low Headroom units, 2x end caps, 2x track stops, all screws and fitting instructions.

Pack No.	Application
HLH250	1 door pack

HARDWARE SPECIFICATION

Track	H250A	Anodised Aluminium (2000, 3000, 4000 & 6000mm lengths) Soffit fix spacing 900mm centres (maximum)
Brackets	H1/SS H5H/SS	Face fixed stainless steel Double face fixed stainless steel (heavy) Starting 20mm from each end of track fix at 900mm centres (max.)
Track Stop	HH5/SS	Anodised aluminium with rubber buffer
Guides	H102SS/94 H105SS/94 H106HSS/94	Timber doors - wall mounted and multiple run guide Timber doors - face mounted guide Timber doors - concealed fixing with SS bearing
Channels	H94X H94 H94P H94PSC	Aluminium (2000, 3000, 4000 & 6000mm lengths) Brass (4000 & 6000mm lengths) Polypropylene (2000, 3000, 4000 & 6000mm lengths) Aluminium supporting channel and polypropylene (2000, 3000, 4000 & 6000mm lengths)
Accessories		
Interlocking Seal	H59BZ/4800 H59CA/4800	Bronze anodised (4800mm to suit typical 2400mm door height) Clear anodised aluminium (4800mm to suit typical 2400mm door height) Drilled and countersunk. Includes brush seal. Refer to Components Section for more information



NOT TO SCALE

