



Model with basic equipment.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Universal voltage
- Screw-in Terminal / plug-in connection
- Compatible with current mortise locks
- Compatible with ProFix® 1 striking plates
- Optimized sliding ramp for a smooth interplay with latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data	
Voltage	10-24 V AC/DC
DIN direction	Universal
Adjustable latch (FF, FaFix®)	Yes
Fail-locked	Yes
Break-in resistance	3750 N
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Installation position	vertical and horizontal
Load cycles for in-plant test	250000
Suitability for fire protection	No
Continuous duty	11-13 V DC
Rated resistance	43 Ohm
Rated current consumption 12 V DC	280 mA
Rated current consumption 24 V DC	560 mA
Rated current consumption 12 V AC	250 mA
Rated current consumption 24 V AC	500 mA
Max. latch preload AC	200 N (12V)
Max. latch preload DC (stabilised)	50 N (12V)
AC current consumption	250 mA (12V)
Current consumption DC (stabilised)	280 mA (12V)
EAN-Number	
4042203558007	
Article number	
118.10-----A71	