

### Product description

Model contains a monitoring contact as potential-free changeover contact. This is actuated by the latch bolt via a slide. The electric strike also features a mechanical permanent unlocking system for the electric strike latch.

### Overview of Advantages

- Suitable for all common striking plates
- Due to 180° fitting, can be used DIN right and left
- Symmetric casing design with fitted monitoring contact
- DIN right, monitoring contact fitted underneath
- Screw-on attachment material: Brass

### Technical data

Handing	Universal
potential	8-16 V AC/DC
Adjustable latch (FF, FaFix®)	Yes
Monitoring contact (RR)	Yes
Mechanical unlocking (E)	Yes
Fail-locked	Yes
Contact loading capacity	1 A
Rated resistance	22 Ohm
Current consumption AC 12 V	470 mA
Current consumption AC 16 V	620 mA
Current consumption AC 8 V	310 mA
Current consumption DC (50% Residual ripple) 12 V	520 mA
Current consumption DC (50% Residual ripple) 16 V	690 mA
Current consumption DC (50% Residual ripple) 8 V	350 mA
Current consumption DC (stabilized) 12 V	550 mA
Current consumption DC (stabilized) 16 V	730 mA
Current consumption DC (stabilized) 8 V	360 mA
Break-in resistance	3500 N
Height	83 mm
Width	20 mm
Depth	28 mm
Operating temperature range	-15 °C to +40 °C
Max. latch preload AC operation 8 V	60 N
Max. latch preload AC operation 12 V	150 N
Max. latch preload AC operation 16 V	150 N
Max. keep pre-load DC (50% Residual ripple) 8 V	80 N
Max. latch preload DC (50% ripple) 12 V	50 N
Max. latch preload DC (50% ripple) 16 V	50 N
Max. latch preload DC (stabilised)	10 N

Article number	17RRE-----R11
----------------	---------------

