




Product description

- OneSystem sash lock N1500 according to EN 12209 for single-leaf doors, product- specific environmental product declaration (EPD) according to EN 15804 with article-specific parameters / tested for 1,000,000 cycles and 300 kg door weight

Characteristics

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 15 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Latch DIN left/right reversible without tools
- Closed lock case at the top and bottom
- Stainless steel faceplate
- Security fittings and oval roses can be screwed on through the lock
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Technical data

Bolt throw	20 mm
Latch	DIN L/R (symmetrical face plate)
Standards	EN 12209
Distance	92 mm (prepared for Euro profile cylinder), 94 mm (prepared for Swiss round cylinder)
Backset	25, 30, 35, 40, 45 mm
Handle follower	8 mm
Front plate	U-shaped face plate: U6 x 24 mm Flat face plate: F3 x 20 mm, F3 x 24 mm, R3 x 20 mm, R3 x 24 mm
Material faceplate	Stainless steel

Variants that can be ordered

Order number	Front plate	Face plate length	Distance
N150000085*0009	F3 x 20 mm	270 mm	92 mm
N150000085*0008	F3 x 24 mm	270 mm	92 mm
N150000085*000R	R3 x 20 mm	270 mm	92 mm
N150000085*000Y	R3 x 24 mm	320 mm	92 mm
N150000085*000F	U6 x 24 mm	320 mm	92 mm
N150000089*0009	F3 x 20 mm	270 mm	94 mm
N150000089*0008	F3 x 24 mm	270 mm	94 mm
N150000089*000R	R3 x 20 mm	270 mm	94 mm
N150000089*000Q	R3 x 24 mm	270 mm	94 mm
N150000089*0018	U6 x 24 mm	270 mm	94 mm
N150000089*000E	F3 x 20 mm	320 mm	94 mm
N150000089*0001	F3 x 24 mm	320 mm	94 mm
N150000089*000Z	R3 x 20 mm	320 mm	94 mm
N150000089*000Y	R3 x 24 mm	320 mm	94 mm
N150000089*000F	U6 x 24 mm	320 mm	94 mm