

iDFace Max

Facial identification access controller

With a modern design and premium facial identification technology, iDFace Max from Control iD enables efficient monitoring and control of people entering and exiting high-traffic buildings.



Touchless

Secure facial recognition with liveness detection enables fast, contactless access - even with masks



Flexible

Choose from face, PIN, RFID, or QR code identification to suit different users and access scenarios



Connected

Built-in connectivity and intercom combine access control and communication in one device



Intuitive

Touchscreen interface and web-based software simplify setup and management

Technical specifications



Access control

Number of users	More than 200,000 registered users
Number of faces	Up to 100,000 faces* with face liveness detection
Access rules	According to schedules and departments
Door control	Via external access control module and/or internal relay 1 REX button input, 1 open door sensor
Relay output	1 internal relay and 1 relay on the external access control module rated up to 30 VAC / 5A
Wiegand input / output	1 / 1 port on the external access control module



Interconnectivity

Ethernet	1 native 10/100 Mbps Ethernet port
USB	1 USB 2.0 Host port
OSDP / RS-485	OSDP support as a peripheral device via RS-485 interface
Wi-Fi	Wi-Fi connection module*
SIP intercom	Integrated G.711-compatible SIP intercom (Pro)*



Identification methods

Facial identification	Two 1080p Full HD cameras (visible light and infrared light)
Proximity reader*	MIFARE® or 125 kHz ASK or HID
Password	User identification through PIN and password
QR code	User identification through QR code



User interface

Display	7" TFT color LCD display (800 x 1280 px) with capacitive touchscreen
Integrated web software	Complete access control management from your browser
Audio	Built-in speaker and microphone



General characteristics

Dimensions (W x H x D)	Terminal: 119.4 x 247 x 34.6 mm External access control module: 52 x 52 x 22 mm
Equipment weight	Terminal: 950 g External access control module: 35 g
Power input	External 12V 2A source or PoE (IEEE802.3af)
Ingress protection rating	IP65



Certifications

Markets	CE FCC UKCA ISED*
---------	-------------------------

* optional / available on select models